2014



HARDWARE COMPONENTS

HARDWARE COMPONENTS











Adjustable Cabinet Legs





Wooden Dowel







Drawer Slides

Latches & Catches

Power Center Grommets







Hinges (Piano-Continuous)

TV Wall Mounts



Adjustment Knobs





ADHESIVES & HOT MELT	GROMMETS
	Executive Series (Metal & ABS)263
ADJUSTMENT KNOBS279	Outlet Accessory266
ANCHORS (Toggler®)301	Oval Wire Management265
BEAUTY SALON STEEL HARDWARE	Power Center274-275
Blow Dryer Holder Ring267	Rectangular Wire Management265
	Round Wire Management264
Flat Iron Holder267	Trash Liners (Stainless Steel)267
	Trash Receptacle (Plastic)267
BUMPON™ PROTECTIVE PRODUCTS (3M™)282-284	HIDEACORD®269
BUSHINGS (All-Fit Adjustable)270	HINGES
CABINET COMPONENTS286	Cabinet324-331, 342
CABINET LEGS	Corner
A La Carte & Components285	Dampers331
Adjustable Metal & ABS285	Euro342
	Flat (Plastic)333
	Institutional330
COMPUTER ACCESSORIES313	Lift-Up (Gas Spring)342
	Non-Mortise Cylinder331
	Panel (Plastic)333
COVER CAPS (Fast Cap Self Adhesive)290	Piano (Continuous Steel)334
DOWELS & DOWEL PINS	Plastic
Furniture	Soft Stay Up342
	Specialty329
	Tee (Plastic)333
	HOLE PLUGS (Nylon Locking)270
DRILL BIT SYSTEM (Flush Mount)290	
	Arrow Clips299
	Canoe Clips
GLUE & STAPLE BLOCKS286	Furniture & Cabinet295-296
GROMMET ACCESSORIES	Furniture Assembly300
	Ratchet Assembly Post & Screw299
GROMMETS	Row Boat Clips299
	Tree Clips
Flactuical Tuina Diagram (Fact Cons)	LATCHEC & CATCHEC

CITCHINETO	
Executive Series (Metal & ABS)	263
Outlet Accessory	266
Oval Wire Management	265
Power Center	
Rectangular Wire Management	265
Round Wire Management	264
Trash Liners (Stainless Steel)	
Trash Receptacle (Plastic)	
HIDEACORD®	269
HINGES	
Cabinet	324-331, 342
Corner	329
Dampers	331
Euro	
Flat (Plastic)	333
Institutional	330
Lift-Up (Gas Spring)	342
Non-Mortise Cylinder	331
Panel (Plastic)	333
Piano (Continuous Steel)	334
Plastic	332-333
Soft Stay Up	342
Specialty	329
Tee (Plastic)	333
HOLE PLUGS (Nylon Locking)	270
JOINERS & FASTENERS	
Arrow Clips	299
Canoe Clips	
Furniture & Cabinet	295-296
Furniture Assembly	
Ratchet Assembly Post & Screw	
Row Boat Clips	299

LOCKS	.310-311
MIRROR CLIPS	289
NON-SKID PADS	
PANTRY/CABINET PULL-OUT HARDWARE	.322-323
POLYURETHANE ADHESIVE BUMPERS	
POWER CENTER GROMMETS	.274-275
POWER GROMMETS	.272-278
QUIK TRAY ROLL OUT SYSTEM	.320-321
RETAINER (Adjustable Panel/Glass)	
RETAINER (Panel)	
RETAINING BUTTONS (Glass/Panel)	288
RETAINING CLIPS (No Route Glass/Panel)	288
REVOLVING TURNTABLES (Lazy Susans)	303
SCREW COVER CAPS	
SCREWS (Flat & Pan Head Particle Board)	300
SHELF RESTS (Plastic, Glass, Steel)	.280-281
STEM BUMPERS (Lexan & Butyrate)	291
SUGATSUNE HARDWARE	
Lateral Opening Door Hinge	340
Lid Stay	337
Soft Close Dampening Hinge	335
Soft Closing Lid Stay	.338-339
Soft Down Stays	
Swing Lift Mechanism	341
SWIVELS	303
TABLE COMPONENTS	
TAPES (Double Coated Adhesive)	
TV LIFTS (Flat Screen)	
TV WALL MOUNTS (Plasma/LCD)	
VENTS (Metal & Plastic)	
WASHERS (Finishing)	300
WEDGES	
WINDOW SHUTTER PINS	
WIRE MANAGEMENT EXTRUSIONS	269

EXECUTIVE SERIES GROMMETS



Cover has snap in mechanism with bristle hair cable management opening 2 sizes available





Two piece square cover with wire management slot gives a sleek modern look





Cover has snap in mechanism with removable flexi-cap management opening 2 sizes available













The CEO executive grommet




Drill Hole Size



Two piece square cover with bristle hair cable management opening slot





METAL

	NUMBER	PART #	*FINISH	A (DIAMETER)	B (DEPTH)	C (DRILL HOLE SIZE)
		M-60P*	Polished Chrome (PC)	2-5/8" (68mm)	55/64" (21.6mm)	2-3/8" (60mm)
	1	M-80P*	Satin Nickel (SN) Stainless Steel (SS)	3-15/32" (88mm)	55/64" (21.6mm)	3-1/8" (80mm)
2	0	M-60E*	Polished Chrome (PC)	2-5/8" (68mm)	13/16" (21mm)	2-3/8" (60mm)
	2	M-80E*	Brushed Nickel (B*)	3-1/2" (90mm)	13/16" (21mm)	3-1/8" (80mm)

ABS

Polished Chrome *(PC), Varnished Aluminum *(AL), Matte Black *(BK)

		Α	В	С	
NUMBER	PART #	(DIAMETER)	(DEPTH)	(DRILL HOLE SIZE)	
3	P-C80* 3-45/64" (94mm)		55/64" (21.6mm)	3-1/8" (80mm)	
4	P-M80* 3-43/64 (93mm)		55/64" (21.6mm)	3-1/8" (80mm)	
5 P-J80* 3-3/4" (95mm)		55/64" (21.6mm)	3-1/8" (80mm)		

ROUND WIRE MANAGEMENT GROMMETS

26 SERIES: TELEPHONE WIRE GROMMETS

PRODUCT FEATURES:

- Material: ABS
- 1-1/8" overall diameter







PART#	DRILL HOLE DIAMETER	COLOR
26BK	1"	Black
26\MH	1"	\\/hito

FLEXI SERIES


PRODUCT FEATURES:


- Material: ABS
- *Color: Black (BK), Silver Gray (SG), White (WH), Brown (BR), Gray (GR), Almond (AL), and Beige (BE)
- Easy maneuvering of wires

PART#	SIZE
G31-*	60mm
G32-*	80mm









31 SERIES

PRODUCT FEATURES:

- · Material: ABS
- · Each set contains a grommet, grommet cap & a slot cover; slot cover stores under cap & out of sight when system is in use

PART #	DRILL HOLE DIA.	COLOR
31DG	2"	Dove Gray
31BR	31BR 2" Brow	
31BK	2"	Black
31PT	2"	Putty
31WH	2"	White






35 SERIES

PRODUCT FEATURES:

- Material: ABS. Includes retractable/self-storing slot cover
- When closed, cover offers a flat profile with neat, uniform surface & shape; open position provides large enough opening with easy access for cover retrieval or removal of entire cap system from grommet

		DRILL	
	PART#	HOLE DIA.	COLOR
35DG		2-3/4"	Dove Gray
35BR 35BK		2-3/4"	Brown
		2-3/4"	Black
	35PT	2-3/4"	Putty
	35WH	2-3/4"	White




* Fits 2-3/4" hole; 3" is dia. dimension.



ECONO SERIES

PRODUCT FEATURES:

- · Material: ABS
- · Color: Black • Textured Cap
- 1" Depth







PRODUCT FEATURES:

- · Material: ABS
- · Easy access to wires. Simply push down on door with finger and slide to the left or right.
- Black (BK) or Silver (SL) top
- One piece construction, no lost tabs or cap
- 7/16" Depth



DRILL PART# HOLE DIA. SPG60-BK 2-5/16" SPG60-SL 2-5/16"





GROMMET HOLE CUTTERS

SAFE - DURABLE - SHATTER RESISTANT

- Electronically fused steel to carbide tip makes a tough, strong tool you can be proud to own!
- · Carbide tipped deep throat hole saws are designed to safely extend the usual range of your portable drill, drill press and lathe. For fast, easy production cutting of abrasive construction materials such as fiberglass, plywood, plasterboard, transite, flakeboard, fiberboard & wood. You can expect this saw to outlast 5 regular saws. Arbor uses a 1/4" pilot drill.



1-3/4" DEEP CUTTING **CUTS**

PART #	INSERTS FOR:
FHC-2 (2")	#31-2" Round
FHC-275 (2-3/4")	#35-3" Round
FHC-4125 (4-1/8")	#37 Wine Ring
FHC-2125	2-1/8" Dia.
FHC- 225 (57mm)	2-1/4" Dia.

ARBOR:

PART# FHA-335

ROUND WIRE GRIPPING GROMMETS

PRODUCT


FEATURES: · Material:

High Impact Styrene

1-1/4"

• Fits into 1-1/8" diameter hole

PART #	COLOR
27BR	Brown
27BK	Black
27WH	White



OVAL WIRE MANAGEMENT GROMMETS


39 SERIES

PRODUCT FEATURES:

- Material: Polystyrene Can fit over sized cords
- 3-1/2" x 2" overall
- Can handle multiple cords







PART#	COLOR	Α	В	С	D	E
39BK	Black					
39WH	White	3-1/2"	3-1/4"	9/16"	2"	1-3/4"
39GR	Gray					

OV32 SERIES



PRODUCT FEATURES:


- Material: ABS
- Color: Black

D

· Can close wire doors when not in use



`I.D.



PART#	Α	В	С	D	E
OV32-BK	5"	4.65"	.98"	2.77"	2.38"

SUPER SIZED GROMMET

PRODUCT FEATURES:

- Material: ABS
- · Color: Black
- 2 parts with removable cap and elongated tab



Depth: 17.5mm (.70").

Routing Dimensions: 65.5mm (2.62") x 156.5mm (6.26").

PART# SSG4214-BK



RECTANGULAR WIRE MANAGEMENT GROMMETS





32 SERIES

1.671"


- Deep bushings designed for wood furniture with wider insert legs for desks or table tops 1-1/4" thick; shallow version for metal furniture applications includes a "variable gauge" bushing that snaps into the cutout and is secured by 4 pins
- Streamlined in appearance and accommodates a 1-7/8" x 3-1/4" cutout with 5/16" radius corners
- Perfect for most business machine leads, coaxial computer cables and telephone cords

17.156





CAP #2 (CIRCULAR)




PART#	CAP STYLE	COLOR	Α	В	С	D	Е
32BK-4	Oval (-4)	Black	3-1/2"	3-1/4"	5/8"	2"	1-7/8"
32BKD-2	Oval (-4) Round (-2)	Black	3-1/2"	3-1/4"	1-7/16"	2"	1-7/8"



33 SERIES: PAPER SLOT GROMMET

PRODUCT FEATURES:

- Material: ABS
- 2 insert depths included (3/4" -1-13/16" & 1"-1/16")
- Color: Black
- Accommodates paper up to 17"



MULTI-WIRE GROMMETS



*Other colors available. Please inquire. Minimums apply.

PRODUCT FEATURES:

- · Material: ABS
- Black*
- 4 Removable tabs for a variety of wire management options

Overall Dimensions:

52mm (2.08") x 104mm (4.16").

Depth: 15.5mm (.62"). **Routing Dimensions:** 45mm (1.80") x 98mm (3.92").

PART#

MWG5214-BK


FAST CAP ELECTRICAL TRIM RING





PRODUCT FEATURES:

- Material: ABS
- Clean up electrical cut outs
- Available for single or double gang boxes
- 1-1/4" depth with trim lines every 1/4"



PART#	DESCRIPTION	*COLOR
ETR-S-*	Single	White (WH), Black (BK),
ETR-D-*	Double	Almond (AL), & Hardrock Maple (HM)

坐FastCap®


DUALLY GROMMET






PRODUCT FEATURES:

- Material: ABS
- Finishes both sides of the hole
- Fits material thickness 3/4" to 2-1/2"
- Trimmable Markings every 1/4"





PART#	*COLOR	Α	В	С
DG25-*	White (WH), Black (BK), Almond (AL), & Hardrock Maple (HM)	3-11/32"	2-1/2"	2-1/2"


OUTLET ACCESSORY GROMMET



PRODUCT FEATURES:

- Material: Styrene
- 4-7/16" x 6-7/16" overall
- 11/16" Deep
- 3-13/16" x 5-13/16" hole size

PART#	COLOR
G1032-BK	Black
G1032-WH	White




STAINLESS STEEL TRASH LINERS



Material- 304 Stainless Steel

PRODUCT FEATURES:

- Brushed finish
- Perfect for use in restaurants, doctor's offices, hospitals, boats, RV's and public restrooms.
- · Overlapping trim edge gives professional finished look.





Other Sizes Available -Please Inquire



PART#	DIAMETER	HEIGHT
TL-061		1"
TL-062	6" 10"	2"
TL-066		6"
TL-101		1"
TL-102		2"
TL-121	12"	1"

PLASTIC TRASH RECEPTACLE GROMMET





38 SERIES Material: Polystrene

PART#	DIAMETER	COLOR
38BK	6"	Black
38WH	6"	White





2 New Finishes FOR HAZMAT & RECYCLABLES WASTE



DRILL HOLE						
PART #	ART# DIAMETER					
38GR	6"	Green				
38RD	6"	Red				

BEAUTY SALON STEEL HARDWARE



Material: 304 Stainless Steel

PRODUCT FEATURES:

- Polished Stainless
- Super strong
- Multiple styles available for maximum storage ability



BLOW DRYER HOLDER RING

• Holds nozzle up to 3" in diameter

PART# BSH-BD3







PART# BSH-CU15



IRON RING


• Holds iron up to 2" in diameter

CURLING

PART# BSH-CU2

FLAT IRON HOLDER

Holds standard size irons (2-1/4" to 2-1/2")





PART# **FINISH** Brushed Stainless **BSH-FL**

CABLE CLAMPS



NATURAL NYLON





These nylon cable clamps are perfect for applications in electronics, automotive, air craft, appliance and many other industries. The Standard Series has a 3/8" wide contact area and is designed for medium to lightweight applications.

* USE #10 PANHEAD FOR ALL

HEAVY DUTY

PART#	D	W	H *	Ε
HDCC-018	3/16"	1/2"	.203	.425
HDCC-025	1/4"	1/2"	.203	.410
HDCC-031	5/16"	1/2"	.203	.500
HDCC-037	3/8"	1/2"	.203	.530
HDCC-050	1/2"	1/2"	.203	.595
HDCC-062	5/8"	1/2"	.203	.655
HDCC-075	3/4"	1/2"	.203	.780
HDCC-100	1"	1/2"	203	910

STANDARD

PART#	D	w	н	E
CC-0187	3/16"	3/8"	.140 (#6)	.430
CC-0250	1/4"	3/8"	.167 (#8)	.410
CC-0312	5/16"	3/8"	.167 (#8)	.495
CC-0375	3/8"	3/8"	.167 (#8)	.595
CC-0500	1/2"	3/8"	.167 (#8)	.605


Larger Sizes Available up to 1-1/2"

QUICK RELEASE CABLE CLAMPS


NATURAL NYLON WITH ADHESIVE

These adhesive backed nylon wire & cable clips are used to route wire & cables. The parts are backed with polyurethane foam tape & feature a releasable clip so wires can be removed after assembly if desired.






*Also available in Black.




PART #	SIZE
AWC-0125	1/8"
*AWC-0375	3/8"



TENSII E

NYLON CABLE TIES




			DUINDLE DIA.	ILINOILL
PART #	COLOR	LENGTH	MIN – MAX	STRENGTH
NCT-400	Natural	4"	1/16" - 7/8"	18 lbs.
NCT-400BK	Black	4"	1/16" - 7/8"	18 lbs.
NCT-550	Natural	5-1/2"	1/16" - 1-1/4"	40 lbs.
NCT-550BK	Black	5-1/2"	1/16" - 1-1/4"	40 lbs.
NCT-800	Natural	8"	1/16" - 2-1/8"	40 lbs.
NCT-800BK	Black	8"	1/16" - 2-1/8"	40 lbs.
NCT-1500	Natural	15"	1/16" – 4"	50 lbs.
NCT-1500BK	Black	15"	1/16" - 4"	50 lbs.

BUNDLE DIA

WIRE MANAGEMENT EXTRUSIONS

8 FT. LENGTHS Black PVC 0.780 ADHESIVE TAPE 1.140 PART# 2243-BK






PART# 5230-BK



WIRE & CABLE ORGANIZATION CHANNEL

- 8 FT. LENGTHS Black Virgin Vinyl


to store and organize wire, computer cable, phone/fax lines, electrical cords and other wiring devices on such items as entertainment centers. computer work stations, desks & home theater systems



PART# CWM15-BK 2.340" 1.090" .753"


LOCK CLOSE CHANNEL

PART #	Α	В	С	BOX QTY
CWM30-BK	.770"	.410"	.143"	800'
CWM50-BK	1.010"	.550"	.194"	672'
CWM10-BK	1.510"	.770"	.242"	320'



1" CLIPS

PART #	DESCRIPTION	Α	В	С
CWM15-BK32	Black Open 1" Clip w/adhesive	2.34	1.09	0.753
CWM10-BK32	Black Lock Close 1" Clip w/adhesive	1.51	0.77	0.242



- Folds into a rigid PVC channel for wire or cable installations
- Easy for storage for up to 50 ft. and 100 ft. of raceway
- · Low cost-High quality
- Perfect for around windows and doors
- Adhesive backing for fast-easy installation
- UL94VO Rated flame retardant PVC

	PART #	DESCRIPTION
	FWF-25511	1/4" White
	FWF-25521	1/4" Beige
	FWF-14511	3/8" White
	FWF-14521	3/8" Beige
	FWF-05511	1/2" White
	FWF-05521	1/2" Beige
	FWF-10511	1" White
	FWF-10521	1" Beige
	PART #	DESCRIPTION
_	FWF-14111	3/8" White
Γ.	FWF-14121	3/8" Beige
	FWF-05111	1/2" White
	FWF-05121	1/2" Reige

HIDEACORD®

SELF ADHESIVE ELECTRICAL WIRE COVER SYSTEM





Foam Adhesive

- 8 Ft. Lengths.
- Rigid ABS Plastic.
- Available In White & Black (Can Be Painted To Match Wall Colors).
- Installs In Minutes.
- Can Be Used On Walls, Baseboards, Ceilings, Etc.
- · No Tools Required.
- · Simple And Easy To Use.

PART#	DESCRIPTION		
1300-WH	102cm Wire Cover-White w/Adhesive		
1300-BK	102cm Wire Cover-Black w/Adhesive		

WE USE ONLY HIGH QUALITY, GENERAL USE ADHESIVE TAPES. EACH CUSTOMER ASSUMES RESPONSIBILITY OF TESTING THE PRODUCT FOR THEIR SPECIFIC APPLICATION. WE WILL SUPPLY SAMPLES FOR THIS PURPOSE. SPECIAL NEEDS CAN BE ACCOMMODATED ON A PER RUN BASIS.

NYLON LOCKING HOLE PLUGS




- DESIGNED WITH MULTIPLE LOCKS TO SNAP IN PANEL THICKNESSES FROM 1/64"-1/8".
- USED TO CLOSE EXCESS CHASSIS HOLES, WIRING OUTLETS & PRODUCTION ACCESS HOLES.
- SUITABLE FOR CRITICAL OR ELEVATED TEMPERATURE APPLICATION.
- CAN ALSO BE USED FOR WOOD PANEL.
- HEAT STABILIZED NYLON (UL94V2).
- ABS FLAMMABILITY RATING (94-HB).

CLEAR

	CHASSIS DIMENSIONS		PART DIMENSIONS	
	HOLE	MAXIMUM	Α	В
PART #	DIA.	THICKNESS	HEAD DIA.	THICKNESS
MP-1000CL	1"	1/8"	1.125	.453

BLACK OR WHITE All available in Black, or add a "W" for White.



	CHASSIS DIMENSIONS		PART DIMENSIONS	
		MAXIMUM	Α	В
PART #	HOLE DIA.	THICKNESS	HEAD DIA	THICKNESS
MP-0187	3/16"	1/16"	.250	.234
MP-0250	1/4"	1/16"	.312	.312
MP-0312	5/16"	1/16"	.375	.312
MP-0375	3/8"	1/8"	.468	.406
MP-0437	7/16"	1/8"	.531	.406
MP-0500	1/2"	1/8"	.578	.406
MP-0562	9/16"	1/8"	.656	.406
MP-0625	5/8"	1/8"	.718	.406
MP-0750	3/4"	1/8"	.922	.406
MP-0875	7/8"	1/8"	1.016	.453
MP-1000	1"	1/8"	1.203	.453
MP-1093	1-3/32" - 1-7/32"	1/8"	1.218	.453
MP-1187	1-3/16"	1/8"	1.312	.453
MP-1250	1-1/4"	1/8"	1.375	.453
MP-1375	1-3/8"	1/8"	1.500	.453
MP-1500	1-1/2"	1/8"	1.672	.453
MP-1750	1-3/4"	1/8"	1.906	.453
MP-2000	2"	1/8"	2.140	.453

LOCKING VENTED HOLE PLUGS

All available in Black, or add a "W" for White.

PART #	HOLE DIA.	MAXIMUM THICKNESS	A HEAD DIA.	B THICKNESS
MP-0750V	0.750"	0.125"	0.906"	0.406"
MP-0875V	0.875"	0.125"	1.1016"	0.453"
MP-1000V	1.00"	0.125"	1.203"	0.453"

REMOVABLE VENTED NYLON PLUGS AVAILABLE, PLEASE INQUIRE!







DADT #	HOLE	В	C	MAN VAUDE
PART #	DIAMETER	HEAD DIA.	THICKNESS	MAX WIRE
AF-0625	5/8"	0.718"	0.406"	0.437"
AF-0750	3/4"	0.859"	0.390"	0.500"
AF-0812	13/16"	0.890"	0.390"	0.500"
AF-0875	7/8"	0.937"	0.453"	0.562"
AF-1000	1"	1.062	0.453"	0.750"
AF-1093	1-3/32"	1.156"	0.453"	0.812"
AF-1250	1-1/4"	1.360"	0.453"	0.875"



REACH & ROHS

REACH & ROP COMPLIANT

PLASTIC VENT GRILLES



Material: Styrene

Available in *White (WH), *Black (BK) or *Silver Gray (SG)

Designed to provide air circulation where needed



G-1970-* Shown in White, Black and Silver Gray

PART #	OVERALL SIZE	HOLE SIZE	MOUNTING TYPE
G-1970-*	2-5/8" x 8-7/8"	2-3/8" x 8-5/8"	Glue On
G-1971-*	3-9/16" x 9-11/16"	2-5/8" x 8-31/32"	Screw Mount
G-1972-*	3-9/16" x 9-11/16"	2-5/8" x 8-31/32"	Glue On
G-1975-*	2-7/8" x 8-3/4"	2-7/16" x 8-3/8"	Glue On



ROUND PLASTIC VENTS

Material: Styrene

Available in *White (WH), *Black (BK), or *Silver (SG)

PART#	OVERALL DIA.	DRILL HOLE DIA.	HEIGHT
G-200-*	2-3/8"	2"	5/8"
G-250-*	2-11/16"	2-1/2"	3/4"
G-300-*	3-3/8"	3"	3/4"

Designed to provide air circulation where needed













PART # O.D. I.D. THICKNESS
SAM-45 1.8125 1.641" .2047"
SAM-60 2.359 2.109" .2362"

3.062"

0.2441"

Material: 304 Sta	inless Steel
Satin fin	nish

0.4 fine mesh wire diameter Screws included



PART #	O.D.	I.D.	THICKNESS
SAD-150	5.906" x 1.578"	5.65" x 1.339"	0.2441"
SAD-200	7.891" x 1.969"	7.638" x 1.732"	0.2441"







3-344

SAM-85

INDUSTRIAL VENTS



Screws not included








	PART#	LENGTH	WIDTH	THICKNESS
Α	1-1122	8-15/32"	4-1/8"	.2362"
В	1-1212	4-17/32"	4-17/32"	.2362"
С	1-2211	8-15/32	4-1/8"	.2362"
D	1-2222	8-15/32"	8-15/32"	.2362"

POWER STATION

3.5"

3.00"









PRODUCT FEATURES:

- · Black ABS construction.
- Equipped with 8 ft. of 14 AWG cable and a grounded plug.
- Works with material thickness of 3/4" to 3".
- · Unit locks in it's upper most position.

		O2R
PART #	OUTLETS	DATA
PDS-96P	3	-
PDS-96US	2	2

POWER DISTRIBUTION CENTER (120V)

3.5" diameter. Pull up for easy access.



PRODUCT FEATURES:

- Black ABS construction.
- Compact
- Inexpensive and easy to install.
- Adaptable installation.
- Only vertical or horizontal data strip on the market today!







- PRODUCT FEATURES:Equipped with 8 ft. of SJT 4 AWG3C heavy duty power cord.
- Attached spring clips for easy installation.
- 2 self powered USB ports, and 1 pass through USB port for data transmission.
- Bore Hole: 3-3-16" x 1-7/16" for installation.
- Overall size: 3-1/2" x 1-3/4".

PART# PDC-96





PRODUCT FEATURES:

- Equipped with 8 ft. of AWG 14 cable and a grounded plug.
- Recess mount and secure with 2 screws. (Not Included)
- 3 AC outlets.2 USB ports for charging.
- Bore hole: 7-3/8" x 1-3/4"
- Overall size: 8-1/4" x 2-1/4".

PART# PDC-224

POWER HUB



in a snap. Keep work surface clear, because all wires can be put away

when task is complete.



PRODUCT FEATURES:


- · Black ABS construction.
- 3 USB ports.
- 2 card readers.
- Microphone port.
- Headphone port.

PART#

PDH-96

directly computer





POWER - I -DOCK (120V)

getting inside.



All in one dock station that allows you to charge, view, listen, and synchronize your iPod / iPhone!

Note: Dock adapter maybe required for use with this unit. Refer to your devices owner manual.





PRODUCT FEATURES:


- · Black ABS construction.
- iPod / iPhone audio / video output for amplifier / tv.
- Charges iPod / iPhone.
- Synchronizes with PC / MAC.
 Apple certified "Made for iPod" and "Works with iPhone" universal dock.
- · Each unit includes: 8' long x 120V power adapter.
- 8' long USB cable.
- · 8' long audio / video cable.
- 30 pin connector

PART# **PDI-96**



from getting inside.





"Made for iPod" and "Made for iPhone" mean that an electronic accessory has been designed to connect specifically to iPod or iPhone, respectively, and has been certified by the developer to meet apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries.

POWER CENTER GROMMETS


Horizontal Power Docks • cUlus 120V

- All units constructed of anodized aluminum frames and black polycarbonate and ABS interfaces.
 - Equipped with 10 ft. of AWG 14 Cable and a grounded plug.
 - Resettable circuit breaker switch rated at 15A.
 - LED power master switch turns unit on and off.



FEATURE:

- Units are easily mounted using a rectangular cut out in the desk surface.
- Secures in position with two sturdy ratchet clips.
- Can be locked in the open position at 45° or 60° to allow easy access.
- Can be closed to recessed position leaving only the cables visible from the desk surface.
- Works with maximum material 2-3/8" and a minimum of 5/8".





FEATURE:

- Clamps onto work surface, no cut out needed.
- Portable.
- Works with maximum material 2" and a minimum of 3/8".



Recess Power Docks								
	OVERALL	CUT OUT	CUT OUT		DATA *			
PART #	LENGTH	LENGTH	WIDTH	OUTLETS	PORTS			
PDG-H-22D	8.86"	9.8"	5.2"	2	2			
PDG-H-32D	10.83"	11.77"	5.2"	3	2			
PDG-H-52D	14.76"	15.70"	5.2"	5	2			

Clamp On Power Docks								
PART#	LENGTH	WIDTH	OUTLETS	DATA* PORTS				
PDG-CL-22D	8.86"	2.56"	2	2				
PDG-CL-32D	10.83"	2.56"	3	2				
PDG-CL-52D	14.76"	2.56"	5	2				

* DATA PORTS ARE OPEN RECEPTACLES ONLY. <u>MUST BE FIELD WIRED!</u> OTHER COLOR OPTIONS AND DATA PORT CONFIGURATIONS AVAILABLE - PLEASE INQUIRE.

POWER CENTER GROMMETS

Vertical Mount Power Docks • cUL us 120V

RETRACTABLE AND CONCEALED POWER OUTLET SYSTEM.



- All units constructed of anodized aluminum with black or gray polycarbonate and ABS interfaces.
- Equipped with 10 ft. of AWG 14 Cable and a grounded plug.
- Resettable circuit breaker switch rated at 15A.
- LED power master switch turns unit on and off.
- Slim 4" diameter Fits into an (80 mm) 3.2" hole.
- Installs easily using a locking ring held firmly in place from the underside of the unit.
- Works with a maximum material thickness of 1-3/4", minimum of 5/16".
- Unit locks in its upper most position.
- Standard with a splash proof, water resistant seal when in the recessed position.





	Vertical Mount Power Docks								
Ī		OVERALL	RECESSED	EXTENDED		DATA*			
	PART #	LENGTH	CLEARANCE	HEIGHT	OUTLETS	PORTS	COLOR		
	PDG-V-32D	14"	14"	9"	3	2	Anodized/Gray		
	PDG-V-3W	12"	12"	7"	3	-	Anodized/Black		


* DATA PORTS ARE OPEN RECEPTACLES ONLY. MUST BE FIELD WIRED!
OTHER COLOR OPTIONS AND DATA PORT CONFIGURATIONS AVAILABLE - PLEASE INQUIRE.

FLAT SCREEN TV LIFT

Available in Silver or Black • 120V







- Simple and fast moving.
- Includes RF remote control, manual/push switch, VESA compatible mounting bracket & larger models include lid lifter.
- Ships in one carton.
- Assembly required simply install in cabinet and plug & play.
- Not just for TV's...suitable for many other applications.
- All units offer reverse function lift.


PART#	COLOR	MINIMUM HEIGHT	MAXIMUM HEIGHT	TRAVEL	DEPTH BEHIND TV	WEIGHT CAPACITY	FUNCTION WEIGHT CAPACITY
WT-4056	Silver	25.5"	43.5"	18"	2"	110 lbs.	45 lbs.
WT-700	Black	23.5"	51"	27.5"	2-13/16"	145 lbs.	60 lbs.
WT-4050	Black	34"	63.5"	29.5"	2-3/4"	145 lbs.	60 lbs.
WT-1000	Black	29.5"	69"	39.375"	2-13/16"	145 lbs.	60 lbs.

NOTE: Reverse function allows lifts to be used in both ascending & descending applications.



LCD WALL MOUNTS

POWDER COATED STEEL • POWDERED COATED CAST ALUMINUM



	PART#	TV SIZE	WEIGHT CAPACITY	FINISH	PROJECTION	PIVOT	VESA	PLATE SIZE
Α	TVL-FM	12"-42"	70 lbs	Powder Coated Black/ Steel	1/2" off Wall	N/A	75 x 75 & 100 x 100	5-1/2" x 5"H
В	TV-SFM	12"-27"	25 lbs	Powder Coated Silver/Cast Aluminum	2" (Arm can extend 1")	160 [^] Horizontally 45 [^] Vertically	75 x 75 & 100 x 100	1-3/4" x 6-3/4"H
С	TV-DPM	12"-27"	27 lbs	Powder Coated Silver/Cast Aluminum	1-1/2" to 9-1/2"	180 [^] Horizontally 45 [^] Vertically	75 x 75 & 100 x 100	1-3/4" x 6-3/4"H
D	TV-APM	15"-30"	30 lbs	Powder Coated Black, Aluminum & Steel	3" -16-1/2"	180 [^] Horizontally 7 degrees up 15 degrees down	45 x 45, 75 x 75 & 100 x 100	2-1/2" x 8-1/4"H
Е	TV-TDM	12"-24"	25 lbs	Powder Coated Black & Chrome Cast Aluminum	9" Rod Extension	Drops down 105° and swivels 180°	75 x 75 & 100 x 100	2-1/4" x 5-3/4"H

PLASMA / LCD FIXED MOUNT FOR FLAT PANEL TV'S

POWDER COATED BLACK/HEAVY GAUGE STEEL

This universal mounting system fits most large flat panel plasma and LCD TVs. Mounts flat to the wall. Made of steel. Locks in place! VESA *compliant.


- · Holds 30" 63" TVs, up to 165 lbs.
- Features locking cleats to keep TV safe and secure to wall.
- Its low profile allows TV to be mounted only 1.25" off the wall.
- Mounting plate is 32" wide.

· All mounting hardware included.

PART# TVPL-FM



It is recommended to always mount into a wood or metal stud using appropriate anchors.



POWER STRIPS

ANGLED POWER STRIPS (120V)

BY ELIMINATING CUTOUTS SHOW OFF YOUR BACKSPLASH OR SHOWCASE WITHOUT THE INTERRUPTION OF OBTRUSIVE OUTLETS AND EXTENSION CORDS!











White (WH)

Brushed Nickel (BN)

WIRE ENTRY

When purchasing 12"

or 18" APS series you must specify left or

right wire entry.

L = Left Wire Entry

R = Right Wire Entry

All other sizes have a


so that wiring can be

done in the field.




Black (BK)

Brown (BR)







APS SERIES


PART#	*FINISH	RECEPTACLE	LENGTH	# OF OUTLETS
APS-12-* (L OR R)	BK, BR, BN	Black	12"	2
APS-12-* (L OR R)	WH	White	12"	2
APS-18-* (L OR R)	BK, BR, BN	Black	18"	3
APS-18-* (L OR R)	WH	White	18"	3
APS-24-*	BK, BR, BN	Black	24"	4
APS-24-*	WH	White	24"	4
APS-30-*	BK, BR, BN	Black	30"	4
APS-30-*	WH	White	30"	4
APS-36-*	BK, BR, BN	Black	36"	4
APS-36-*	WH	White	36"	4


TAMPER RESISTANT OUTLET






Meets 2008 National Electric Code **Screws Provided**





Brushed Nickel (BN)







TR SERIES

PART #	*FINISH	RECEPTACLE	LENGTH	# OF OUTLETS
TR-12-*	BN	Gray	12"	2
TR-12-*	DR	Black	12"	2
TR-12-*	SW	White	12"	2
TR-18-*	BN	Gray	18"	4
TR-18-*	DR	Black	18"	4
TR-18-*	SW	White	18"	4
TR-24-*	TR-24-* BN		24"	4
TR-24-*	DR	Black	24"	4
TR-24-*	SW	White	24"	4
TR-30-*	BN	Gray	30"	4
TR-30-*	DR	Black	30"	4
TR-30-*	SW	White	30"	4
TR-36-*	BN	Gray	36"	4
TR-36-*	DR	Black	36"	4
TR-36-*	SW	White	36"	4
				_

Other lengths, and finish/receptacle combinations are available. Please inquire.

It is recommended that all electrical products be installed by a licensed electrician.


ADJUSTMENT KNOBS

- COLOR BLACK
- Constructed of durable nylon or polypropylene knobs with zinc plated steel studs and inserts.
- Designed for economical, light-duty securing and clamping applications.
- Resistant to water and solvents.



STYLE	PART#	DIAMETER	THREAD SIZE	TYPE	STUD LENGTH	MATERIAL
	S7-F13BK	1.125"	1/4-20	Male	.75"	Nylon
	S7-F10BK	1.575"	5/16-18	Female	N/A	Polypropylene
	S7-F15BK	2.36"	5/16-18	Female	N/A	Polypropylene
	S7-F14BK	1.575"	1/4-20	Male	1.375"	Polypropylene
1	S7-F17BK	1.575"	5/16-18	Male	.50"	Polypropylene
	S7-F18BK	1.575"	5/16-18	Male	.75"	Polypropylene
	S7-F19BK	1.575"	5/16-18	Male	1.375"	Polypropylene
	S7-F20BK	2.36"	5/16-18	Male	.50"	Polypropylene
	S7-F21BK	2.36"	5/16-18	Male	.75"	Polypropylene
	S7-N12BK	1.575"	1/4-20	Female	N/A	Polypropylene
	S7-N13BK	2.36"	5/16-18	Female	N/A	Polypropylene
	S7-N22BK	1.575"	1/4-20	Male	.75"	Polypropylene
	S7-N23BK	1.575"	1/4-20	Male	1.375"	Polypropylene
2	S7-N24BK	1.575"	5/16-18	Male	.50"	Polypropylene
	S7-N25BK	1.575"	5/16-18	Male	.75"	Polypropylene
	S7-N26BK	1.575"	5/16-18	Male	1.00"	Polypropylene
	S7-N27BK	1.575"	5/16-18	Male	1.375"	Polypropylene
	S7-N28BK	2.36"	5/16-18	Male	.75"	Polypropylene
	S7-N29BK	2.36"	5/16-18	Male	1.50"	Polypropylene
	S7-K14BK	1.575"	5/16-18	Female	N/A	Polypropylene
	S7-K15BK	2.36"	5/16-18	Female	N/A	Polypropylene
	S7-A30BK	1.575"	1/4-20	Male	.75"	Polypropylene
	S7-A31BK	1.575"	1/4-20	Male	1.375"	Polypropylene
3	S7-A32BK	1.575"	5/16-18	Male	.75"	Polypropylene
3	S7-A33BK	1.575"	5/16-18	Male	.50"	Polypropylene
	S7-A34BK	1.575"	5/16-18	Male	1.00"	Polypropylene
	S7-A35BK	1.575"	5/16-18	Male	1.50"	Polypropylene
	S7-A36BK	2.36"	5/16-18	Male	.75"	Polypropylene
	S7-A37BK	2.36"	5/16-18	Male	1.50"	Polypropylene
4	S7-C21BK	1.25"	1/4-20	Male	.75"	Nylon
5	S7-I31BK	2.50"	1/4-20	Female	N/A	Nylon
6	S7-J21BK	1.375"	1/4-20	Male	.75"	Nylon

SHELF RESTS



To calculate shelf length, use the following formula: inside cabinet width - shelf clearance = shelf size

PLASTIC SHELF RESTS

LOCKING SHELF RESTS (Fluted)

Designed to hold shelves securely in place











Pin Length

Pin Diameter

Overall Lenath

Width w/o Pin

								SHELF	SHELF
	PART #	COLOR	MATERIAL	Α	В	С	D	THICKNESS	CLEARANCE
1	JPE-301-12-010-1	White	ABS	1/4"	5/16"	2-1/4"	1/2"	1/2"	1/4"
	JPE-301-34-010-1	White	ABS	1/4"	5/16"	2-1/4"	1/2"	3/4"	1/4"
	JPE-301-58-010-1	White	ABS	1/4"	5/16"	2-1/4"	1/2"	5/8"	1/4"
2	R25-192-750WH	White	H.D.P.E	5mm	5/16"	2-1/4"	1/2"	3/4"	7/32"
	R25-604-500-CL	Clear	Polycarbonate	1/4"	5/16"	1-3/4"	1/2"	1/2"	7/32"
3	R25-604-625-CL	Clear	Polycarbonate	1/4"	5/16"	1-7/8"	1/2"	5/8"	7/32"
	R25-604-750-CL	Clear	Polycarbonate	1/4"	5/16"	2"	1/2"	3/4"	7/32"
	R25-805-500-CL	Clear	Polycarbonate	5mm	1/4"	1-3/4"	1/2"	1/2"	7/32"
4	R25-805-625-CL	Clear	Polycarbonate	5mm	1/4"	1-7/8"	1/2"	5/8"	7/32"
	R25-805-750-CL	Clear	Polycarbonate	5mm	1/4"	2"	1/2"	3/4"	7/32"
	OPHS-1826-BK	Black	Nylon 6	5mm	15/64"	1-11/16"	1/4"	1/2"	3/16"
	OPHS-1826-BR	Brown	Nylon 6	5mm	15/64"	1-11/16"	1/4"	1/2"	3/16"
5	OPHS-1826-WH	White	Nylon 6	5mm	15/64"	1-11/16"	1/4"	1/2"	3/16"
Э	OPHS-1826-CL	Clear	Polycarbonate	5mm	15/64"	1-11/16"	1/4"	1/2"	3/16"
	OPHS-1828-CL	Clear	Polycarbonate	5mm	15/64"	1-11/16"	1/4"	5/8"	3/16"
	OPHS-1829-CL	Clear	Polycarbonate	5mm	15/64"	1-11/16"	1/4"	3/4"	3/16"
	R25-244-625WH	White	H.D.P.E	5mm	3/8"	1-5/8"	1/2"	5/8"	7/32"
6	R25-244-750WH	White	H.D.P.E	5mm	3/8"	1-7/8"	1/2"	3/4"	7/32"
	R25-244-750BE	Beige	H.D.P.E	5mm	3/8"	1-7/8"	1/2"	3/4"	7/32"



INSTITUTIONAL LOCKING SHELF REST (Smooth)

- Over 300 pound shear test
 Supports shelf loads over 500 lbs
- For extra support, this can be screwed to the side panel of the cabinet
- Ideal for commercial or institutional furniture
- Can withstand earthquakes

CHELE

SHELF

 PART #
 COLOR
 MATERIAL
 A
 B
 C
 D
 SHELF THICKNESS CLEARANCE

 R25-BGD-CL
 Clear
 Polycarbonate
 Twin 5mm
 5/16"
 2-1/2"
 1/2"
 3/4" or 1"
 1/4"



SPOON SHAPE SHELF REST (Fluted)

PART #	COLOR	MATERIAL	Δ	В	С	D	CLEARANCE	=
R25-171CL			1/4"	5/16"	1/2"	1/2"	3/16"	Ī



SPOON SHAPE SHELF REST w/SMOOTH PIN for SOFT WOOD (Smooth)


							SHELF
PART #	COLOR	MATERIAL	Α	В	С	D	CLEARANCE
R25-170CL	Clear	Polycarbonate	1/4"	13/32"	1/2"	1/2"	3/16"







STANDARD DUTY SHELF RESTS (Fluted) PART # COLOR MATERIAL A B C D C









MEDICINE CABINET SHELF REST (Smooth)

Accepts up to 1/8" shelf and designed so that the shelf will not shimmy

							SHELF	SHELF
PART#	COLOR	MATERIAL	Α	В	С	D	THICKNESS	CLEARANCE
R25-CK	Clear	Polycarbonate	5MM	5/16"	1/2"	1/2"	1/8	3/16"




SMOOTH PIN SHELF REST IDEAL FOR SOFT WOOD (Smooth)

								SHELF
	PART #	COLOR	MATERIAL	Α	В	С	D	CLEARANCE
ı	R25-809WH	White	H.D.P.E.	5MM	3/8"	1/2"	1/2"	5/64"

IF YOU ARE LOOKING TO COVER SHELF REST HOLES, SEE PAGE 290 FOR OUR FASTCAP™ SELECTIONS

SHELF RESTS



To calculate shelf length, use the following formula: inside cabinet width - shelf clearance = shelf size

PLASTIC SHELF RESTS



STEEL PIN SHELF REST w/PLASTIC HOUSING (Smooth)

								SHELF
PAR	Γ#	COLOR	MATERIAL	Α	В	С	D	CLEARANCE
R25-72	8CL	Clear	Brite Nickel Pin w/Polycarbonate Housing	5MM	1/4"	1-1/4"	3/8"	3/16"



2 PIECE 32mm SHELF LOCKING SYSTEM

Holds shelf in place

PART#	COLOR	MATERIAL	Α
SH-103113	White	Nylon	5MM



GLASS SHELF RESTS

								SHELF	SHELF
P	ART#	COLOR	MATERIAL	Α	В	С	D	THICKNESS	CLEARANCE
R25	-605CL	Clear	H.D.P.E.	1/4"	3/8"	7/8"	1/2"	3/16"	1/8"
R25	-606CL	Clear	H.D.P.E.	1/4"	3/8"	7/8"	1/2"	1/4"	1/8"
R25	5-806CL	Clear	H.D.P.E.	5mm	3/8"	7/8"	1/2"	1/4"	1/8"



							SHELF
PART#	FINISH	MATERIAL	Α	В	С	D	CLEARANCE
SH-138	Brite Nickel	Nickel Plated w/PVC Nonskid Pad	5mm	5/16"	1"	11/16"	1/8"

STEEL SHELF RESTS

SHELE

SHELE



		RESTS

								SHELF
	PART #	FINISH	MATERIAL	Α	В	С	D	CLEARANCE
	R25-228-NI	Bright Nickel	Steel	5MM	5/16"	3/4"	7/16"	1/8"
1	R25-228-BRS	Bright Brass	Steel	5MM	5/16"	3/4"	7/16"	1/8"
	R25-228-BZ	Bronze	Steel	5MM	5/16"	3/4"	7/16"	1/8"
2	R25-128-NI	Bright Nickel	Steel	1/4"	3/8"	7/8"	1/2"	1/8"
2	R25-128-BRS	Bright Brass	Steel	1/4"	3/8"	7/8"	1/2"	1/8"
3	R25-450NP-SS	Bright Nickel	Steel	7MM	3/8"	15/16"	9/16"	1/8"
3	R25-450BRS-SS	Bright Brass	Steel	7MM	3/8"	15/16"	9/16"	1/8"

STEEL SHELF RESTS w/SOFT BROWN PVC SLEEVE



PART#	FINISH	MATERIAL	Α	В	С	D	CLEARANCE
R25-300-NI		Steel w/Brown PVC Sleeve	1/4"	7/16"	1-1/4"	3/4"	1/8"
R25-300-BR	0	Steel w/Brown PVC Sleeve	1/4"	7/16"	1-1/4"	3/4"	1/8"
R25-305-NI		Steel w/Brown PVC Sleeve	5mm	7/16"	1-1/4"	3/4"	1/8"
R25-305-BR	Bright Brass	Steel w/Brown PVC Sleeve	5mm	7/16"	1-1/4"	3/4"	1/8"

ZINC DIECAST SPOON SHELF RESTS



							SHELF
PART #	FINISH	MATERIAL	Α	В	С	D	CLEARANCE
SH-700Z	Bright Nickel	Zinc Diecast	1/4"	7/16"	1"	5/8"	1/8"
SH-700B	Bright Brass	Zinc Diecast	1/4"	7/16"	1"	5/8"	1/8"

STRAIGHT DOWEL SHELF RESTS



	PART #	FINISH	MATERIAL	Α	В	С	D	CLEARANCE
ĺ	PSR-02CH	Bright Nickel	Steel	5mm	5/16"	11/16"	N/A	1/8"
	PSR-02BR	Bright Brass	Steel	5mm	5/16"	11/16"	N/A	1/8"

HOLE GROMMETS

- Designed to be used in shelf rest holes as a decorative accent
- This accepts a specific size shelf rest, therefore the drill hole will need to be slightly larger
 NO BROKEN BOXES- 1000 pcs. minimum order



PART #	FINISH	MATERIAL	PIN DIAMETER	OVERALL SIZE
R25-450NP-GT	Bright Nickel	Steel	7mm	1/2" Dia. x 1/4" High
R25-450BRS-GT	Bright Brass	Steel	7mm	1/2" Dia. x 1/4" High
R25-128BRS-GT	Bright Brass	Steel	1/4"	5/16" Dia. x 1/4" High
R25-128NI-GT	Bright Nickel	Steel	1/4"	5/16" Dia. x 1/4" High


3M™ BUMPON™ PROTECTIVE PRODUCTS

EXCELLENT FOR GLASS TABLES, CABINET DOOR, LIDS & DRAWERS!


Bumpons products are make of durable, resilient polyurethane polymer formulated especially for its unique high coefficient of friction, slip-resistant, non-marring features. An aggressive, high tack pressure sensitive adhesive protected with any easy release liner makes application fast & easy. Use to prevent slamming, nicking, scuffing, sliding, vibration or noise. Clear bumpons become virtually invisible, since the clarity of the polyurethane bumpers enables them to transmit any color they are placed on.



- NON-SKID
- NON-MARRING
- CRACK RESISTANT
- SELF ADHESIVE BACKING




CLEAR



DIMENSIONS:

			ENGLISH	METRIC		
	PART#		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
^	SJ-5302	WIDTH:	0.312	7.9	Bell Shaped	Clear
A	30-3302	HEIGHT:	0.085	2.2	Dell Shapeu	Clear
В	SJ-5303	WIDTH:	0.44	11.1	Hemisphere	Clear
В	30-3303	HEIGHT:	0.20	5.0	пеннарнете	Clear
_	SJ-5306	WIDTH:	0.375	9.5	Hamianhara	Claar
C	30-3300	HEIGHT:	0.150	3.8	Hemisphere	Clear
D	SJ-5308	WIDTH:	0.50	12.7	Tapered Square	Clear
ט	30-3300	HEIGHT:	0.12	3.1	rapered Square	Clear
_	SJ-5312	WIDTH:	0.50	12.7	Cylindrical	Clear
	30-3312	HEIGHT:	0.14	3.5	Cylindrical	Cleai
F	SJ-5318	WIDTH:	0.50	12.7	Tapered Square	Clear
_	30-3310	HEIGHT:	0.23	5.8	rapered Square	Ciear
G	SJ-5382	WIDTH:	0.250	6.4	Hemisphere	Clear
G	5J-5382	HEIGHT:	0.075	1.9	пеннізрпете	Ciear

QUIET CLEAR SERIES



DIMENSIONS:

		_		ENGLISH	METRIC		
	PAR	RT #		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
^	A SJ	6506	DIAMETER:	0.375	9.5	Hemispherical	Clear
	A 33	33-0300	HEIGHT:	0.150	3.8	riemisphencai	Cleai
	B SJ-6512	6E12	DIAMETER:	0.500	12.7	Cylindrical	Clear
	D 33	33-6312	HEIGHT:	0.140	3.5	Cylindrical	Cleal
	C SJ-6553		WIDTH:	0.433	11.0	Hexagonal	Clear
	C 33	-0555	HEIGHT:	0.120	3.05	Cone	Cleal
	D 61	SJ-6561	LENGTH: 0.433		11.0	Hexagonal Hemisphere	Clear
	D 33		HEIGHT:	0.150	3.8	nexagonal nemisphere	Clear

BRIGHT WHITE



DIMENSIONS:

		ENGLISH	METRIC		
PART #		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
A SJ-5412	WIDTH:	0.507	12.7	Cylindrical	Bright White
A 33-3412	HEIGHT:	0.14	3.6	Cylindrical	Bright write


^{*} THE ITEMS LISTED AS WHITE ARE AN OFF WHITE COLOR. THE BRIGHT IS PURE WHITE IN COLOR.


3M™ BUMPON™ PROTECTIVE PRODUCTS

EXCELLENT FOR GLASS TABLES, CABINET DOOR, LIDS & DRAWERS!


DIMENSIONS:

COLORS





C, D & L



	DIMENSIONS.		-			
	DADT "	ENGLISH (ASS)		METRIC	OTV// E	001.00
	PART#		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
A	SJ-5001BK	WIDTH: HEIGHT:	0.50 0.14	12.7 3.5	Cylindrical	Black
В	SJ-5003WH SJ-5003GY SJ-5003BK	WIDTH: HEIGHT:	0.44 0.20	11.1 5.0	Hemisphere	*White Grey Black
С	SJ-5007BK	WIDTH: HEIGHT:	0.40 0.12	10.2 2.5	Tapered Square	Black
D	SJ-5008WH SJ-5008GY SJ-5008BK	WIDTH: HEIGHT:	0.50 0.12	12.7 3.1	Tapered Square	*White Grey Black
E	SJ-5009WH SJ-5009GY SJ-5009BK	WIDTH: HEIGHT:	0.88 0.40	22.3 10.1	Circular Depressed	*White Grey Black
F	SJ-5012WH SJ-5012GY SJ-5012BR SJ-5012BK	WIDTH: HEIGHT:	0.50 0.14	12.7 3.5	Cylindrical	*White Grey Brown Black
G	SJ-5017WH SJ-5017BK	WIDTH: HEIGHT:	0.75 0.38	19.0 9.6	Hemisphere	*White Black
н	SJ-5018WH SJ-5018GY SJ-5018BR SJ-5018BK	WIDTH: HEIGHT:	0.50 0.23	12.7 5.8	Tapered Square	*White Grey Brown Black
ı	SJ-5023WH SJ-5023GY SJ-5023BK	WIDTH: HEIGHT:	0.81 0.30	20.5 7.6	Tapered Square	*White Grey Black
J	SJ-5027WH SJ-5027GY SJ-5027BK	WIDTH: HEIGHT:	0.63 0.31	16.0 7.9	Hemisphere	*White Grey Black
K	SJ-5076BK	WIDTH: HEIGHT:	.315 0.11	8.0 2.8	Cylindrical	Black
L	SJ-5508BK	WIDTH: HEIGHT:	0.50 0.12	12.7 3.1	Tapered Square	Black
M	SJ-5514WH SJ-5514GY SJ-5514BK	WIDTH: HEIGHT:	0.81 0.52	20.6 13.1	Tapered Square	*White Grey Black
N	SJ-5705BK	WIDTH: HEIGHT:	1.25 0.24	31.75 6.1	Tapered Square	Black
0	SJ-5744BK	WIDTH: HEIGHT:	0.75 0.16	19.1 4.1	Cylindrical	Black

HEAVY DUTY



	DIMENSIO	NS:			
		ENGLISH	METRIC		
PART #		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
SJ-5532BR	WIDTH:	1.88	47.7	Circular Depressed	Brown
SJ-5532BK	HEIGHT:	.66	16.7	Circular Depressed	Black





	DIMENSIO	NO.			
		ENGLISH	METRIC		
PART #		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
SJ-5510BK	WIDTH:	0.50	12.7	Ctrin	Plack
SJ-5510WH	HEIGHT:	0.15	3.8	Strip	Black


^{*} THE ITEMS LISTED AS WHITE ARE AN OFF WHITE COLOR. THE BRIGHT IS PURE WHITE IN COLOR.

3M™ BUMPON™ PROTECTIVE PRODUCTS

EXCELLENT FOR GLASS TABLES, CABINET DOOR, LIDS & DRAWERS!


TOP HAT





DIMENSIONS:						
	PART#	Α	В	С	STYLE	COLOR
Α	SJ-6115	.625	.093	.187	Flat Top Hat	Black
В	SJ-6125	.625	.093	.187	Round Top Hat	Black

EASY SLIDE BUMPER



- NON-MARRING & NON-STAINING
- CRACK RESISTANT
- SELF ADHESIVE BACKING
- LOAD BEARING UP TO 40 LBS. PER BUMPER

DIMENSIONS:

		ENGLISH	METRIC		
PART #		+/-0.02 in.	+-/0.5 mm	STYLE	COLOR
SJ-6344BK	WIDTH: HEIGHT:	.75 .16	4.1 19.1	Cylindrical	Black

POLYURETHANE ADHESIVE BUMPERS



All bumpers stocked in clear. Please inquire for colors. Colors sold in full cases only. 1000 PIECE MINIMUM ORDER

			CASE
PART #	WIDTH	HEIGHT	QUANTITY
PAB-001CL	.500"	.140"	5000
PAB-002CL	.312"	.085"	5400
PAB-003CL	.440"	.200"	5082
PAB-006CL	.375"	.150"	7200
PAB-008CL	.500"	.120"	5000
PAB-009CL	.880"	.400"	1440
PAB-012CL	.500"	.140"	5000
PAB-018CL	.500"	.230"	5000
PAB-023CL	.810"	.300"	2646
PAB-044CL	.750"	.160"	2450
PAB-078CL	.400"	.118"	7200
SOFT SERIES - So	ftor humbor for	ovtra sound door	doning proportios

OFT SERIES -Softer bumper for extra sound deadening properties PAB-106CL .375" .150" 7200 PAB-112CL .500" .140" 5000



PAB-018

PAB-002

PAB-023



PAB-006



PAB-003



PAB-078

PAB-009

PAB-044

NON-SKID PADS

EMBOSSED BLACK

Our Non-Skid Pads consist of specially formulated thermoplastic rubber material fused to crosslinked polyethylene foam with adhesive backing.

- HIGH DURABILITY
- NON-MARRING
- ABRASIVE RESISTANCE
- CHEMICAL & WATER RESISTANT

Kitchen Appliances Office & Desk Accessories **Computer Terminal Equipment Medical Devices**

DIE-CUTTING AVAILABLE, PLEASE INQUIRE.



50 FT. ROLLS	PART #	DESCRIPTION
	NS-1600-4	1/2" Wide x 1/8" Thick
	NS-1600-2	1/2" Wide x 1/16" Thick
	NS-3200-4	1" Wide x 1/8" Thick
	NS-3200-2	1" Wide x 1/16" Thick

	PICTURE	PART#	DESCRIPTION
		NS-0016-4	1/2" Dia. x 1/8" Thick
		NS-0016-2	1/2" Dia. x 1/16" Thick
		NS-3232-4	1" x 1" x 1/8" Thick
		NS-3232-2	1" x 1" x 1/16" Thick
		NS-3264-4	1" x 2" x 1/8" Thick
		NS-3264-2	1" x 2" x 1/16" Thick
		NS-3296-4	1" x 3" x 1/8" Thick
		NS-3296-2	1" x 3" x 1/16" Thick

ADJUSTABLE CABINET LEGS



METAL LEG SETS



- Adjustable from 4" to 6-1/2"
- Comes packed in sets of 4 legs, 4 black plastic top sockets with bolts, 2 toe kick clips (screw mount or groove mount) 4 white & 4 almond cover caps
- 330 lb. weight capacity per leg

	TOE KICK	
PART #	CLAMP STYLE	
CLG-400S	Screw Mount	
CLG-400G	Groove Mount	



ABS PLASTIC LEG SETS

- Adjustable from either 4-1/2 x 7 or 3.68 to 6.28
- Comes packed in sets of 4 black legs, 4 top sockets & 2 black toe clips
- 330 lb 750 lb, load capacity per leg



PART#	HEIGHT ADJUSTMENT	MATERIAL	LOAD CAPACITY PER LEG	TOE KICK CLAMP STYLE
CLG-445A	4-1/2"-7"	ABS	350 lbs.	Adhesive
OPHS-2609	3.68"-6.28"	Polystyrene	188 lbs.	Screw

A LA CARTE CABINET LEGS & ACCESSORIES



ABS PLASTIC CABINET LEG

- Two piece white leveling leg (foot & shaft)
- 330 lb load capacity per leg

PART #	HEIGHT ADJUSTMENT
CLG-423-4	4" - 4-5/8"
CLG-423-6	6" - 6-5/8"

ABS PLASTIC TOP SOCKETS

- White
- Bolt included



PART# CLG-841



Metal Fingers to ensure long lasting connection to leg




PART #	CLAMP STYLE
CLG-228A	Adhesive Mount
CLG-228G	Groove Mount
CLG-228S	Screw Mount

PLASTIC CABINET COMPONENTS

CORNER PROTECTORS

 Designed to protect vulnerable corners of mirrors, cabinet doors and picture frames



Material: H.D.P.E.

For 3/16" or 1/4" Glass

PART# COLOR
GC-215 White

Material: H.D.P.E.



PART # COLOR CP-448 White

Material: Polyethylene





Accept Up To 1/2" Thick Material
PART # COLOR
GC-500 White

GLUE AND STAPLE BLOCKS

 Stapled inside the cabinet to hold the cabinet backs and sides together during the assembly process




Material: Styrene


250 Pcs. per Box

PART # COLOR R44-445 Beige

Material: Polyethylene











PART # COLOR SIZE R44-250 White 2"

B R44-300 White 3" C R44-400 White 4"

FLOOR GLIDE AND PROTECTOR

New

Material: Polyethylene

- Staple to underside of cabinets or furniture
 Prevents damage to cabinets during handling and
- Prevents damage to cabinets during handling and transportation.
- 1/4" (60mm) of clearance between cabinet and floor

PART # COLOR SIZE R32-737 Natural 1-1/2"



CORNER BRACES

- Designed to strengthened and stabilize the cabinet during the manufacturing process
- To be installed in the top section of the base cabinet and aid in securing the countertop

2.600

Material: H.D.P.E.

PART # COLOR R44-370 White

Material: H.D.P.E.



PART # COLOR CB-2500 White

Material: Polyethylene








PART # COLOR CB-920 White

PLASTIC WEDGE & DOOR STOP

Material: H.D.P.E.

- Wedges are used to assure proper positioning of hinged doors
- Wedges guide doors when case is out of alignment
- Neat appearance, assures doors stay closed, economical & does not require finishing
- May be installed at top or bottom of all doors, side of single doors.





PART # COLOR
R50-441DBR Dark Brown
R50-441WH White


TOE KICK BRACKET



- Material: Styrene

 Designed to stabilize and strengthen the toe kick area of the cabinet
- Staple mount






Accept Up To 1/2" Thick Material
PART# COLOR INSET
TK-880BK Black 4"
TK-960BK Black 4-1/2"

BREAK-AWAY PLASTIC FURNITURE WEDGE







PART# COLOR
58-076-400 Dark Brown


RUBBER-SEALS® W/ PEEL & STICK

114-113 (black only) 500 Ft. Coils w/Adhesive

COLOR Black

114-114 (black only) 500 Ft. Coils w/Adhesive

DR-6-*



COLOR Black

Black

(White where noted)

Sponge Rubber

Recommended Temperature Range for General **Product Applications** -20° through +150°

MANY APPLICATIONS:

Cabinets Doors Windows Camper Shell Doors Skylights Sunroofs and many others

114-1333 (black) 114-1333-OW (off white)


500 Ft. Coils w/Adhesive



COLOR Black White

114-119 (black only) 500 Ft. Coils w/Adhesive

DR-2-*



COLOR Black

EUROPEAN DUST SEAL SYSTEMS

DR-1-* Black (*BK), White (*WH), Brown (*BR) PVC - 8 Ft. Lengths



White (*WH), Almond (*AL) Polypropylene W/Santoprene 1000 Ft. Coils

APPLICATION: DR-1, DR-6, Ø.

> .270 DIA .029

Black (*BK), White (*WH), Brown (*BR), Clear (*CL), Almond (*AL) Dual Durometer/PVC - 8 Ft. Lengths 7/16" WIDE SOFT, ALLOWS EITHER DOOR TO OPEN PEEL & GUIDE FOR ALIGNMENT TO CABINET DOOR APPLICATION

ULTRA PILE DUST SEAL / WEATHERSEAL w/ADHESIVE





GLASS / PANEL RETAINING BUTTONS

FLUSH




PART#

R21-10BE


R21-10BK

R21-10CL

R21-180CL




- Retainers are P.E. plastic. Clear retainers are Lexan plastic.
- Screws sold separately.





		USE
PART #	"A"	SCREW
R21-290	.125	В
R21-292	.250	В

R21-180



Beige

Black

Clear

Clear

COLOR USE SCREW


Α

Α

Α

В






DIA. 9 16	32 7	

	R21 Series Screws			
_	SCREW BULK PART# HEAD/FINISH CTN. QTY.			
A	SCR-5625FHZ	#5 x 5/8" Flat Head Zinc	(20M)	
В	SCR-6625PHZ	#6 x 5/8" Pan Head Zinc	(15M)	
C	SCR-6625FHZ	#6 x 5/8" Flat Head Zinc	(15M)	





R21-183BE Beige



RECESSED







- Retainers are **P.E. plastic**. Clear retainers are **Lexan plastic**.
- They are for semi-permanent installations.
- · Screws sold separately.

_	oo.a oopa.o	USE		
	PART#	COLOR	DIM. "A"	SCREW
	R21-281DB	Dk. Brown	5/16"	С
	R21-281CL	Clear	5/16"	С
	R21-313CL	Clear	1/8"	С

- To fasten: Twist button from side of frame and push back towards screw into locking position.
- To release: Twist and lift button over frame.
- Screws sold separately.

		USE
PART #	COLOR	SCREW
R21-175BE	Beige	Α



GRILLE

- Screw adjustable, secure holding & quick removal of metal grilles.
- Reversible to accommodate varied glass thicknesses and door mortises.
- 7/8" vinyl tipped screw tightens and adjusts without harming glass.

BRONZE FINISH ON STEEL Overall Size: 3/8" wide x 1-3/16" long screws included.

PART #




NO-ROUTE GLASS / PANEL RETAINING CLIPS



- Designed to attach glass or decorative panels to doors without routing.
- Can be screwed or stapled into place.
- Straight and corner pieces available.
- Available for 1/8" or 3/16" thick panels.

		MTL	
PART #	COLOR	THICKNESS	TYPE
R21-1806BR	Brown	1/8"	Straight
R21-1806CL	Clear	1/8"	Straight
R21-1807BR	Brown	3/16"	Straight
R21-1807CL	Clear	3/16"	Straight
R21-1804BR	Brown	1/8"	Corner
R21-1804CL	Clear	1/8"	Corner
R21-1805BR	Brown	3/16"	Corner
R21-1805CL	Clear	3/16"	Corner



ADJUSTABLE PANEL/GLASS RETAINER



Lengths: 12 Ft. Material: RPVC

Accomodates all panels at 1/16", 1/8" & 1/4"


Colors Available

*LB - Light Beige *FW - Frost White *PLT - Platinum


unless otherwise noted

Insert May Be:

- Glass Markerboard Tackboard
- Expanded Metal Grilles
- Woven Wire Grilles
- Decorative MDF Screening Panel



Light



PANEL RETAINER

Lengths: 500 Ft. Coils Material: Vinyl **Colors Available**

*WH - White *BK - Black *BR - Brown

unless otherwise noted

STAPLE TYPE



PART#

102-627-*

1/4'

PART#

102-698-*

1/4"

9/64RAD

1/4

1/16R

3/8

PART#

102-623-*

1/32R

100 Ft. Coils

100 Ft. Coils

100 Ft. Coils











PART# 102-645-*



PART#

102-644-*

PART#

102-624-*

1/16R

PART#










PART# 102-620-*


Lengths: 500 Ft. Coils Material: Vinyl • Use S4 or S10 Slotter

Colors Available

*WH - White *BK - Black *BR - Brown *CL - Clear unless otherwise noted

GROOVE TYPE





102-646-*

MIRROR CLIPS

Designed to attach mirrors, glass, decorative panels, etc. to any flat surface

Clear Diamond Back

• Made of crystal styrene




R45-283CL

Clear

· Made of crystal styrene, ribbed

• Fits 1/4" glass thickness



PART# R45-293CL

Clear

· Made of crystal styrene



FLAT HEAD ZINC SCREWS

PART# SCR-5625FHZ SCR-6625FHZ

PAN HEAD ZINC SCREWS

PART# SCR-6625PHZ

FAST CAP™ SELF ADHESIVE COVER CAPS

とFastCap®

STANDARD

9/16" = 20 Sheets with 52 caps ea. 1040 per box

11/16" = 20 Sheets with 36 caps ea. 720 caps per box

PART#	SIZE	
PVC Solid (Colors	
FCSP916-	9/16"	
FCSP1116-	11/16"	
PVC Wood	Colors	
FCWP916-	9/16"	
FCWP1116-	11/16"	
PVC Metallic		
FCME916-	9/16"	
FCME1116-	11/16"	
Unfinished (Real Wood)		
FCSW916-	9/16"	
FCSW1116-	11/16"	
Prefinished (Re	eal Wood)	
FCPW916-	9/16"	
FCPW1116-	11/16"	

MINI BOX

9/16" = 5 Sheets with 52 caps ea. 260 per box

11/16" = 5 Sheets with 36 caps ea. 180 caps per box

PART#	SIZE
PVC Solid	Colors
FCMB916-	9/16"
FCMB1116-	11/16"
PVC Wood	Colors
FCMB916-	9/16"
FCMB1116-	11/16"
PVC Met	allic
FCMB916-	9/16"
FCMB1116-	11/16"
Unfinished (Re	eal Wood)
FCMB916-	9/16"
FCMB1116-	11/16"
Prefinished (R	eal Wood)
FCMB916-	9/16"
FCMB1116-	11/16"

PRODUCT FEATURES:

- 9/16" (14mm) and 11/16" (18mm) Diameter
- · Available in solid color PVC, PVC wood grain, PVC metallic, Unfinished solid wood and Finished solid wood
- Unlike other caps, these do not depend on the screw for proper installation
- Does not require any additional gluing or calking



(actual sizes)



PVC (Solids, Woodgrains and Metallics)————————————————————————————————————				
White (WH)	Rosewood Oak (SD)	Presidential Walnut (PW)	Select Cherry (SC)	
Antique White (AW)	Medium Oak (MD)	Imperial Walnut (IW)	Medium Cherry (MC)	
Almond (AL)	Light Oak (LO)	Mahogany on Walnut (MW)	Bourbon cherry (BC)	
Black (BK)	Hardrock Maple (HM)	Knotty Pine (KP)	Golden Cherry (GC)	
Fog Gray (DG)	Manitoba Maple (MM)	Beech (BE)	Dark Cherry (DC)	
Folkstone Gray (LG)	White washed Maple (WM)	Finished MDF (MDF)	Heritage Cherry (HT)	
Natural Oak (NO)	Light Maple (LM)	Brushed Brass (BR)	Autumn Cherry (AC)	
Golden Oak (GO)	Clear Maple (CM)	Polished Brass (PBR)	Fuji Cherry (FC)	
Renaissance Oak (RN)	American Maple (AM)	Brushed Chrome (BCHR)	Red Mahogany (RM)	
Pickled Oak (PO)	Natural Cherry (NC)	Polished Chrome (PCHR)	Dark Red Mahogany (RM)	

Unfinished (Real Wood)



Pre-finished (Real Wood)-



FLUSH MOUNT DRILL BIT SYSTEM



- Carbide tipped
- Allows user to drill a pilot hole and countersink
- The drill bits custom stop insures that the surface cannot be marred

DESCRIPTION PART# FCDB-0916-CB 9/16" Drill bit



POP-ON SCREW COVERS & BASES

MATERIAL: POLYPROPYLENE

Pop-On Screw Covers & Bases may be used with flat head nails, countersunk wood screws, self-tapping screws rivets, drive screws, machine screws, washer faced screws and other types of fasteners. They may also be used with metric screws in M4, M4.5 and M6 screw sizes.



POP-ON SCREW COVERS

10 NEW COLORS

NEW: Green, Blue, Orange, Purple, Dark Blue, Light Pink, Forest Green, Red, Turquoise & Yellow. Stock Colors & Metallics Available: Black, White, Brown, Light Gray, Beige, Brite Brass, Brite Chrome, Satin Chrome, Brite Copper & Satin Copper.

- New colors are in stock for SC2-250.
- Polypropylene caps are UV stabilized for outdoor use (<u>does not</u> include metallics).


1			
A	()		С
1			S
1			S
B		N	SI

	DIMENSIONS					
	COVER#	OVER# A B				
	SC2-460	.515	.215*			
	SC2-810	.630	.225*			
N	SC2-250	.700	.260*			

WORKS WITH COVER	BASE#	Α	В	С	D	SCREW SIZE
	SC2-B04P	.115	.415	.120	.275	#4 PAN
SC2-460	SC2-B069	.115	.415	.151	.275	#6 PAN
	SC2-B46F	.115	.415	.151	-	#4/#6 COUNTERSUNK
SC2-810	SC2-B8P	.125	.505	.169	.365	#8 PAN
	SC2-B10P	.125	.505	.195	.365	#10 PAN
	SC2-B810F	.125	.505	.195	-	#8/#10 COUNTERSUNK
SC2-250	SC2-B250P	.125	.620	.245	.490	1/4-20 PAN
302-250	SC2-B250F	.130	.620	.245	-	1/4-20 COUNTERSUNK

All Bases are a Natural Nylon Color

POP-ON SCREW BASES



SCREW COVER CAPS

Standard Screw Cover Caps Only .50 in Diameter

PART# COLOR
SC-1LBR Lt. Brown
SC-1DBR Dk. Brown
SC-1WH White
SC-1BK Black
SC-1AL Almond
SC-1DG Dove Gray

For PHILLIPS or POSI-DRIVE



Petite Screw Cover Caps Only .40 in Diameter

PART #	COLOR
SC-4WH	White
SC-4BK	Black
SC-4BR	Brown
SC-4BE	Beige
SC-4LG	Light Grav


HINGED SCREW COVERS

MATERIAL: POLYPROPYLENE




PART #	COLOR	SCREW SIZE	Α	В
SC3-460BK	Black	#4/#6 PAN	29/64"	3/16"
SC3-460WH	White	#4/#6 PAN	29/64"	3/16"
SC3-460BE	Beige	#4/#6 PAN	29/64"	3/16"
SC3-810BK	Black	#8/#10 PAN	35/64"	13/64"
SC3-810LG	Light Grey	#8/#10 PAN	35/64"	13/64"
SC3-810WH	White	#8/#10 PAN	35/64"	13/64"
SC3-810BE	Beige	#8/#10 PAN	35/64"	13/64"
SC3-250BK	Black	#1/4-20 PAN	45/64"	1/4"
SC3-250WH	White	#1/4-20 PAN	45/64"	1/4"
SC3-250BE	Beige	#1/4-20 PAN	45/64"	1/4"

SCREW PLUG BUTTON



LEXAN AND BUTYRATE STEM BUMPERS




USES: DOORS, BOTTOM of FURNITURE, ETC.



* Pin Diameter Tolerance = +/- .010

PART#	MATERIAL	COLOR
S49-750CL	Lexan	Clear
S49-750BK	Lexan	Black
S49-511CL	Butyrate	Clear
043-3110L	Dutyrate	Oleai



PUSH KNOB LATCHES

SUGATSUNE





BODY



- Knob and latch combined.
- · Non-handed.
- · Low profile.
- Use with door thickness 19/32" 63/64".
- Provides 22 lbs. holding force.
- Ideal for use in RV's and boats. Anywhere space is limited for application.

Material: Zinc Alloy & ABS

SQUARE





DPL-SQ-SN Satin Nickel









ROUND







Chrome

PART# **FINISH** DPL-RO-G Gold **DPL-RO-CR** Chrome

OVAL







PART# FINISH **DPL-OV-G** Gold **DPL-OV-CR** Chrome

NON-MAGNETIC LATCHES & CATCHES

MINI "LIGHT DUTY"

NON-MAGNETIC TOUCH LATCH



MATERIAL: **POLYPROPYLENE HOUSING & CATCH PLATE**

- Push to latch and unlatch
- Screws included

PART #	COLOR	RETAINING FORCE
MC-20BL	Black	8.8 lbs.
MC-20WT	White	0.0 108.

MEDIUM "LIGHT DUTY" NON-MAGNETIC TOUCH LATCH





MATERIAL: ABS HOUSING & CATCH PLATE

- · Push to latch and unlatch
- Screws included

OLOR	RETAINING FORCE
Black	
Brown	17.6 lbs.
Vhite	
	Black Brown

ADJUSTABLE KNUCKLE CATCH



- · Catch force is adjustable by turning screw
- Mounts with #10 Screws (not included)


PUSH IN PULLING PART# **COLOR FORCE FORCE** 3-555-4/BLK Black 29-57 lbs. 18-44 lbs. 1-555-2/WHT White

KNUCKLE CATCH

MATERIAL: WHITE POLYACETAL HOUSING WITH POLYMIDE CATCH PLATE

· Grabs and holds door tightly







		PUSH IN	PULLING
PART #	COLOR	FORCE	FORCE
JC-T50	White	6.6 lbs.	8.3 lbs.
K-CATCH/WHT-T	vvriite	12.5 lbs.	15.6 lbs.

LATCHES & CATCHES



SEALED MAGNETIC CATCHES





- Hermetically sealed for high corrosion resistance.
- · No metal to metal contact, ideal for clean rooms
- Works with screw #8 (not included)





MAGNETIC FORCE PART# COLOR MC-JM45WT 6.6 lbs. White

Polyacetal



	MAGNETIC	
PART #	FORCE	COLOF
MC-JM50/BL	6.6 lbs.	Black
MC-JM50/WT	6.6 lbs.	White



Hermetically sealed strike eliminates metal particles when applied with MC-JM sealed magnetic catches

PART# MC-JMP45

Other plates available please inquire

ULTRA THIN MAGNETIC CATCH



Steel with Nickel finish

- · Ideal for tight spaces
- Max temperature 176°F
- · Strike plate included
- Screws included



MAGNETIC TOUCH LATCHES

ABS housing with Nickel plated steel strike plate





• For single or double doors

PART#

MC-YN001P

- For overlay door allow a 4mm (5/32") gap between door & cabinet frame for pushing room
- Screws included





PART#	COLOR	MAGNETIC FORCE
ML-30W/BRN	Brown	2.6 lbs.
ML-30W/WHT	White	2.6 lbs.

MINI MAGNETIC CATCH

White Polybuthelene housing with Brite Zinc plated strike plate


- · Available in strong or light magnetic force
- · Strike plate included
- Screws Included

ROHS

COMPLIANT



	MAGNETIC
PART #	FORCE
MC-YS001	6.6 lbs.
MC-YS002	2.6 lbs






RECTANGULAR MAGNETIC TOUCH LATCH

ABS housing with Zinc Chromate strike plate


• For overlay door allow a 3.5mm (9/64") gap between door and cabinet frame for pushing room.

Screws included





			MAGNETIC
PART #	COLOR	TYPE	FORCE
ML-80/BLK	Black	Short	3.5 lbs.
ML-80/BRN	Brown	Short	3.5 lbs.
ML-80/WHT	White	Short	3.5 lbs.




PART#	COLOR	TYPE	FORCE
ML-120/BRN	Brown	Long	5.2 lbs.
ML-120/WHT	White	Long	5.2 lbs.

LATCHES & CATCHES

PLASTIC MAGNETIC CATCHES

WITH STRIKE PLATE · MATERIAL: ABS (Unless noted)

MAG-CATCH™ 1 LB. PULL FORCE



- Material: Acrylic DR101 (Clear), ABS (Black)
- Size: 7/8" L x 1/2" H x 3/8" W
- Adhesive mount

Adhesive mount solvent bonds to acrylic, polycarbonate, ABS and styrene. Eliminates unsightly screws or hardware.

> PART# COLOR MC-SM-CL Clear MC-SM-BK Black

8.8 LB. PULL FORCE



Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

• Size: 2-1/4" L x 5/8" W x 1/2" H

PART # COLOR OI-121-BK Black OI-121-WH White

10 LB. PULL FORCE



Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

• Size: 1-13/16" L x 5/8" W x 1/2" H

PART# COLOR OI-150-BK Black

OI-150-BR Brown OI-150-WH White

6.6 LB. PULL FORCE





Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

Size: 5/8" Dia. x 3/4" Long

PART# COLOR OI-132-BK Black OI-132-WH White

DOUBLE MAGNETIC TOUCH LATCH

9 LB. PULL FORCE

• Size: 2-3/8" L x 1-7/8" W x 3/4" H

PART# COLOR

SUPER STRONG MAGNETIC CATCH

12 LB. PULL FORCE

Black

Screws & Strike Plate included

OI-347

MAGNETIC PUSH LATCH 8 LB. PULL FORCE



- Size: 1-3/16" L x 1-7/8" W x 3/4" H
- · Screws included

PART # COLOR OI-346 Black

10 LB. PULL FORCE



- Size: 1-5/8" L x 7/8" W x 5/8" H
- Screws included

PART# COLOR OI-130-BR Brown

26 LB. PULL FORCE



Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

Size: 3-3/8" L x 11/16" W x 9/16" H

PART# COLOR OI-312-BR Brown

OI-418 Brown **ALUMINUM MAGNETIC CATCHES**

• Size: 1-7/8" L x 15/16" W x 15/16" H

PART# COLOR



- **5 LB. PULL FORCE** HEAVY DUTY
 - · Perfect for large cabinet doors
 - Suitable for institutional or commercial cabinets
- Similar to EPCO #592
- Size: 2" L x 1-3/16" W x 13/16" H

PART# OI-332-AL

Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

WITH STRIKE PLATE 9 LB. PULL FORCE



Size: 3-1/8" L x 1" W x 1/2" H

PART# OI-632-AL

Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

Uses Screw

SCR-6625FHZ

#6 x 5/8" Flat Head Zinc

14 LB. PULL FORCE



Size: 3-1/8" L x 1" W x 3/4" H

PART# OI-732-AL

Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

NON MAGNETIC CATCHES

DOOR CATCH with Strike Plate



- · Material: Clear Acrylic
- Size: 5/8" L x 1-5/16" W Adhesive mount

PART# DC-100-CL


DOUBLE BARREL FRICTION CATCH with Strike Plate



White H.D.P.E. Size: 1-3/4" L x 9/16" W x 11/16" H

Uses Screw SCR-6625PHZ #6 x 5/8" Pan Head Zinc PART# 274-167

DOUBLE ROLLER CATCH with Self-Locating Strike Plate



Finishes: Antique Brass & Zinc • Size: 1-3/4" L x 1-1/8" W x 1/2" H

> Uses Screw SCR-6625FHZ #6 x 5/8" Flat Head Zinc

FINISH PART# **OI-781AB** Antique Brass **OI-781Z** Zinc

DOUBLE BALL CABINET CATCH Material: Brass Plated




PART # SIZE OI-881-BC 1-5/8" OI-882-BC 2" OI-883-BC 2-1/4"

FURNITURE/CABINET JOINERS & FASTENERS

MODESTY BLOCK

Material: Nylon

- · Designed to attach modesty panels to desks
- No pre-drilling required, three screw application
- Place block against inside modesty panel & tighten screws; place panel against desk front & tighten third screw from block bottom into desk top




PART # COLOR 6073-BR Brown 6073-WH White

Use #8 flathead screws (see below)

KD BRACKETS

Material: Steel, Zinc Finish



PART #
KD67-ZINC
KD68-ZINC

Use #10 flathead screws (see below)

FURNITURE JOINER HARDWARE

Material: Steel, Zinc Finish




	PART#	DESCRIPTION
	CB-10	1" x 1" x 1/2" x 16 GA.
	CB-15	1-1/2" x 1-1/2" x 1/2" x 14 GA.
CORNER	CB-20	2" x 2" x 5/8" x 14 GA.
BRACES	CB-25	2-1/2" x 2-1/2" x 5/8" x 14 GA.
	CB-30	3" x 3" x 7/8" x 13 GA.
	CB-40	4" x 4" x 7/8" x 13 GA.
FLAT CORNER	FC-30	3" x 3" x 1/2" x 14 GA.

Use #8 flathead screws (see below)

ANGLE BRACKETS

Material: H.D.P.E.





PART # COLOR R44-200BK Black R44-200WH White








PART # COLOR R44-210BK Black R44-210WH White

Use #6 panhead screws (see below)

HF-1 HOOK-IN-FITTINGS

Material: Polycarbonate



Use #8 flathead screws (see below)

FLAT HEAD ZINC SCREWS

PART #	SIZE
SCR-6625FHZ	#6 x 5/8"
SCR-8625FHZ	#8 x 5/8"
SCR-1625FH7	#10 x 5/8"

FASTENERS

K-9 FASTENERS

Material: Nylon Body with Nickel Plated Steel Pin

• Easy to assemble & knockdown without tools or screws





PART # COLOR K-9WH White K-9BR Brown

Use #6 flathead screws (see below)

PAN HEAD ZINC SCREWS


PART # SIZE
SCR-6625PHZ #6 x 5/8"

TITUS® FURNITURE FASTENERS

Titus

20mm EXPANDO-6 HOUSING **NON-OUTRIGGER**

- MATERIAL: Nylon
- Available for 15mm/16mm & 18mm/19mm boards
- "Klix" locking system provides a strong, vibration proof connection
- Available in Almond, Black, White, Brown & Candlelight plastic





SIDE ENTRY







20mm EXPANDO-6 HOUSING **OUTRIGGER**

- MATERIAL: Nylon
- Available for 15mm/16mm & 18mm/19mm boards
- "Klix" locking system provides a strong, vibration proof connection

• Available in Almond, Black, White & Brown plastic



PART#	TYPE
OP6-6435-*	Non-Outrigger Side Entr
OP6-6437-*	Non-Outrigger Side Entr
OP6-6431-*	Non-Outrigger Drop On
OP6-6433-*	Non-Outrigger Drop On
OP6-6443-*	Outrigger Side Entry
OP6-6445-*	Outrigger Side Entry
OP6-6439-*	Outrigger Drop On
OP6-6441-*	Outrigger Drop On

*COLOR **BOARD SIZE** (CHOOSE CODE) 15mm/16mm 18mm/19mm AL = Almond15mm/16mm **BK** = Black 18mm/19mm WH = White 15mm/16mm BR = Brown18mm/19mm **CN** = Candlelight 15mm/16mm 18mm/19mm

5mm DOWELS

- MATERIAL: Steel
- 5mm x 11mm dowel
- · Klix locking system provides a strong, vibration proof connection
- Features an integral skirt which acts as a positive stop during insertion
- Zinc Plated

PIECES PER CARTON PART# **OPHS-6406** 5000



15mm CAM

- MATERIAL: Steel
- For 16mm (.64") & 19mm (.76") board thicknesses
- · Linear cam profile results in smooth, easy cam rotation & dowel pull up
- "Klix" locking feature provides a strong, vibration pro

ation proof joint			
PART #	PANEL SIZE	FINISH	PIECES PER CARTON
OP5-5644B	16mm	Black	2000
OP5-5644Z	16mm	Zinc	2000
OP5-5656Z	19mm	Zinc	2000

FASTENER FOR FACE & EDGE BORING

- One turn lock system, thus reduces assembly time
- Pre-assembled for consumer convenience
- (1") 25mm dia. housing x (1/2") 12.5mm depth











PART#	DESCRIPTION	MATERIAL	PIECES PER CARTON
OPHS-3118	White Housing	Nylon	2500
OP-3118BR	Brown Housing	Nylon	2500
OPHS-3150	White Decorative Cap	Nylon	1000
OPHS-3180	White Hilo Screw Dowel	Steel	2500
OPHS-3168	Euro Screw Dowel - Zinc	Steel	2500

WOODEN DOWEL PINS


White Birch *Available Fluted or Spiral

(*Please Specify Fluted or Spiral When Ordering)

• Kiln Dried To 6-8% Moisture

Which pin is better, Spiral or Fluted?There is no real answer as to which pin offers better holding power. While some manufacturers dowel-inserting machinery may advise which groove suits its machinery better, both pins offer excellent dispersion of glue as well as excellent bonding qualities.





	SIZE: 1/4	4" × 1" (*Flu	ited or Spiral)
PART #	R25-2510C*	R25-2510M*	R25-2510B* (Bulk)
QUANTITY	100 Pcs./Bag	1,000 Pcs./Bag	25,000 Pcs. 100,000 Pcs.
4	SIZE: 1/4"	x 1-1/2" (*)	Fluted or Spiral)
PART #	R25-2515C*	R25-2515M*	R25-2515B* (Bulk)
	100 Pcs./Bag	1,000 Pcs./Bag	25,000 Pcs. 100,000 Pcs.
	S <i>IZE: 1/4"</i>	<i>x 1-3/4"</i> (*)	Fluted or Spiral)
PART #	R25-2517C*	R25-2517M*	R25-2517B* (Bulk)
QUANTITY			25,000 Pcs. 100,000 Pcs.
		4" x 2" (*Flu	. ,
PART #	R25-2520C*		R25-2520B* (Bulk)
QUANTITY			25,000 Pcs. 100,000 Pcs.
		8" x 1" (*Flu	
PART #			R25-3710B* (Bulk)
	100 Pcs./Bag		25,000 Pcs. 100,000 Pcs.
	SIZE: 3/8"		Fluted or Spiral)
	R25-3712C*	R25-3712M*	
	100 Pcs./Bag		25,000 Pcs. 100,000 Pcs.
	SIZE: 3/8"		Fluted or Spiral)
	R25-3715C*		R25-3715B* (Bulk)
	100 Pcs./Bag		25,000 Pcs. 100,000 Pcs.
	SIZE: 3/8"		Fluted or Spiral)
	R25-3717C*		R25-3717B* (Bulk)
QUANTITY	100 Pcs./Bag		25,000 Pcs. 100,000 Pcs.
DADT #		8" x 2" (*Flu	
	R25-3720C*		R25-3720B* (Bulk)
	100 Pcs./Bag SIZE: 3/8"		25,000 Pcs. 100,000 Pcs.
	R25-3725C*		Fluted or Spiral)
	100 Pcs./Bag		R25-3725B* (Bulk) 25,000 Pcs. 100,000 Pcs.
	SIZE: 7/16		Fluted or Spiral)
	R25-4315C*		R25-4315B* (Bulk)
	100 Pcs./Bag		25,000 Pcs. 100,000 Pcs.
	SIZE: 7/16		Fluted or Spiral)
	R25-4317C*		R25-4317B* (Bulk)
			25,000 Pcs. 100,000 Pcs.
GOARTITT	100 1 03./Dag	1,000 1 03./Dag	20,000 1 03. 100,000 1 03.

PART #	R25-4320C*	R25-4320M*	R25-4320B* (Bulk)		
QUANTITY	100 Pcs./Bag	1,000 Pcs./Bag	25,000 Pcs. 100,000 Pcs.		
9	SIZE: 7/16	" x 2-1/2" (*	Fluted or Spiral)		
PART #	R25-4325C*	R25-4325M*	R25-4325B* (Bulk)		
QUANTITY	100 Pcs./Bag	1,000 Pcs./Bag	25,000 Pcs. 100,000 Pcs.		
	SIZE: 7/1	16" x 3" (*Flu	ited or Spiral)		
PART #	R25-4330C*	R25-4330M*	R25-4330B* (Bulk)		
QUANTITY	100 Pcs./Bag		25,000 Pcs. 100,000 Pcs.		
		2" x 2" (*Flut			
PART #		R25-5020M*	R25-5020B* (Bulk)		
			25,000 Pcs. 100,000 Pcs.		
SIZE: 1/2" x 2-1/2" (*Fluted or Spiral)					
PART #	R25-5025C*		R25-5025B* (Bulk)		
QUANTITY			25,000 Pcs. 100,000 Pcs.		
		2" x 3" (*Flut			
	R25-5030C*	R25-5030M*	R25-5030B* (Bulk)		
QUANTITY	100 Pcs./Bag	1,000 Pcs./Bag	25,000 Pcs. 100,000 Pcs.		
		METRIC SIZE			
5					
PART#			S		
PART # QUANTITY	R25-6250C* 100 Pcs./Bag	n x 25mm (* R25-6250M* 1,000 Pcs./Bag	Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs.		
PART # QUANTITY	R25-6250C* 100 Pcs./Bag	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (*	Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral)		
PART # QUANTITY PART #	R25-6250C* 100 Pcs./Bag SIZE: 6mn R25-6300C*	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M*	Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk)		
PART # QUANTITY PART # QUANTITY	R25-6250C* 100 Pcs./Bag SIZE: 6mn R25-6300C* 100 Pcs./Bag	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag	Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs.		
PART # QUANTITY PART # QUANTITY	R25-6250C* 100 Pcs./Bag SIZE: 6mn R25-6300C* 100 Pcs./Bag SIZE: 8mn	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (*	Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral)		
PART # QUANTITY PART # QUANTITY PART #	R25-6250C* 100 Pcs./Bag SIZE: 6mn R25-6300C* 100 Pcs./Bag SIZE: 8mn R25-8300C*	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M*	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk)		
PART # QUANTITY PART # QUANTITY PART # QUANTITY	R25-6250C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-8300C* 100 Pcs./Bag	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M* 1,000 Pcs./Bag	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk) 25,000 Pcs. 100,000 Pcs.		
PART # QUANTITY PART # QUANTITY PART # QUANTITY QUANTITY	R25-6250C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-8300C* 100 Pcs./Bag R25-8300C*	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M* 1,000 Pcs./Bag n x 32mm (*	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral)		
PART # QUANTITY PART # QUANTITY PART # QUANTITY PART # QUANTITY	R25-6250C* 100 Pcs./Bag SIZE: 6mm R25-6300C* 100 Pcs./Bag SIZE: 8mm R25-8300C* 100 Pcs./Bag SIZE: 8mm R25-8300C*	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M* 1,000 Pcs./Bag n x 32mm (* R25-8320M*	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8320B* (Bulk) R25-8320B* (Bulk)		
PART # QUANTITY PART # QUANTITY PART # QUANTITY PART # QUANTITY QUANTITY	R25-6250C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-8300C* 100 Pcs./Bag R25-8320C* 100 Pcs./Bag	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M* 1,000 Pcs./Bag n x 32mm (* R25-8320M* 1,000 Pcs./Bag	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8320B* (Bulk) 25,000 Pcs. 100,000 Pcs.		
PART # QUANTITY PART # QUANTITY PART # QUANTITY PART # QUANTITY PART # QUANTITY	R25-6250C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-8300C* 100 Pcs./Bag R25-8320C* 100 Pcs./Bag R25-8320C*	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M* 1,000 Pcs./Bag n x 32mm (* R25-8320M* 1,000 Pcs./Bag n x 32mm (* R25-8320M*	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8320B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8320B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral)		
PART # QUANTITY PART # QUANTITY PART # QUANTITY PART # QUANTITY PART # QUANTITY	R25-6250C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-6300C* 100 Pcs./Bag R25-8300C* 100 Pcs./Bag R25-8320C* 100 Pcs./Bag R25-8320C* 100 Pcs./Bag R25-8320C*	n x 25mm (* R25-6250M* 1,000 Pcs./Bag n x 30mm (* R25-6300M* 1,000 Pcs./Bag n x 30mm (* R25-8300M* 1,000 Pcs./Bag n x 32mm (* R25-8320M* 1,000 Pcs./Bag n x 35mm (* R25-8350M*	S Fluted or Spiral) R25-6250B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-6300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8300B* (Bulk) 25,000 Pcs. 100,000 Pcs. Fluted or Spiral) R25-8320B* (Bulk) 25,000 Pcs. 100,000 Pcs.		

SIZE: 7/16" x 2" (*Fluted or Spiral)

FURNITURE DOWELS

MODESTY BLOCK

Material: Polyethylene



FURNITURE JOINER HARDWARE

Material: Nylon

For joints stronger than the wood or wood product itself

ELIMINATES GLUING & CLAMPING

- Reduces assembly time
- Insert manually or with most doweling machines
- Not affected by humidity less likely to jam insertion equipment
- · Forced fit no glue necessary



PREMIUM SERIES







DIAMETER					
PART#	x LENGTH	COLOR			
R25-147	6mm x 1-1/8"	Natural			
R25-604	8mm x 1-1/2"	Natural			

R25-860 8mm x 1-1/2" Natural

WINDOW SHUTTER PINS

STANDARD SHUTTER PIN

SIZE

R25-830 8mm x 30mm

PART#

Material: Nylon





- A = Pin Diameter: 0.14"
- B = Head Diameter: .242"
- **C** = Pin Length: .676" **D** = Shoulder Diameter: .306"
- E = Full Length: 1.076"

COLOR

Black


PART# COLOR SP-1 Natural

RETRACTABLE SHUTTER PIN

Material: Polyethylene

• Great for replacements & repairs





- A = Pin Diameter: 0.14" **B** = Head Diameter: .24"
- C = Full Length: .875"

SP-17 White

COLOR


PART#

TENSION CONTROL SHUTTER PIN

Material: Nylon

· Cuts down on loose slats.





- A = Pin Diameter: 0.14"
- B = Head Diameter: .24"
- C = Full Length: 1.08"
- Spring Diameter: 0.255"
- For 2-1/2" louver, use every 3rd slat
- For 3-1/2" louver, use every 2nd slat
- For 4-1/2" louver, use every slat

PART # COLOR SP-19 Natural

FASTENERS

RATCHET ASSEMBLY POST & SCREW

- Polypropylene
- Simply press together these screws with serrated pins for fast and easy assembly
- Works with flat panels, punched papers, key cases, catalogs, etc.
- Not intended for applications requiring removable/reusable fasteners!
- Usable in corrosive environments
- · Will not mark or mar most surfaces








PART #	COLOR	LENGTH
SP-250BK	Black	1/4"
SP-250WH	White	1/4"
SP-375BK	Black	3/8"
SP-375WH	White	3/8"
SP-500BK	Black	1/2"
SP-500WH	White	1/2"
SP-750BK	Black	3/4"
SP-750WH	\/\hite	3/4"

NATURAL NYLON ARROW CLIPS

- Molded natural nylon fasteners offer an inexpensive fast method to hand assemble metal, wood and plastic composition or any other thin gauge materials
- Reusable
- Specially designed body compresses through a pre-punched hole and springs back to shape, locking the assembled parts securely
- Provides a vibration, abrasion and corrosion resistant connection
- · Electrically insulating









		PANEL	HEAD	HEAD		CLIP
PART#	HOLE SIZE	THICKNESS RANGE	DIA. 'D'	HEIGHT 'A'	LENGTH 'B'	DIA. 'C'
AC-001	.182/.192	.062/.125	.360	.060	.400	.225
AC-003	.151/.161	.062/.125	.280	.040	.390	.196
AC-006	.182/.192	.310/.330	.370	.060	.540	0.225
AC-009	.250/.260	.125/.187	.484	.060	.575	.290
AC-015	.118/.122	.062/.125	.280	.060	.390	.150
AC-016	.250/.260	.360/.380	.610	.065	.810	0.286

OTHER SIZES AVAILABLE - PLEASE INQUIRE

PLASTIC FASTENERS





CANOE FASTENERS

CELCON Black & White



		HOLE		HEAD	WORK
PART #	COLOR	SIZE	SHAFT	DIA.	THICKNESS
PF6-20BK	Black	3/16"	5/8"	13/32"	.228
PF6-20WH	White	3/16"	5/8"	13/32"	.228
PF6-31BK	Black	3/16"	5/8"	27/64"	.325
PF6-31WH	White	3/16"	5/8"	27/64"	.325

ROW BOAT FASTENERS

HDPE Black & White

- Fits hole size 1/4"
- Fits work thickness 1/4"



PART # COLOR
CF8-20BK Black
CF8-20WH White

TREE FASTENERS

NYLON Black, White & Gray

Used for one-time applications & is purposely difficult to remove





		HOLE		HEAD	WORK
PART #	COLOR	SIZE	SHAFT	DIA.	THICKNESS
PF8-16BK	Black	1/4"	1/2"	11/16"	.180220
PF8-16WH	White	1/4"	1/2"	11/16"	.180220
PF8-20BK	Black	1/4"	5/8"	11/16"	.180380
PF8-20WH	White	1/4"	5/8"	11/16"	.180380
PF8-20GY	Gray	1/4"	5/8"	11/16"	.180380
PF8-24BK	Black	1/4"	3/4"	11/16"	.180570
PF8-28BK	Black	1/4"	7/8"	11/16"	.180700
PF8-32BK	Black	1/4"	1"	11/16"	.180820

FLAT & PAN HEAD PARTICLE BOARD SCREWS

Flat Head Screws

Zinc or Black Phillips Drive, Coarse Thread



Pan Head Screws


Zinc or BlackPhillips Drive,
Coarse Thread

PART #	FINISH	SIZE	BULK CTN QTY.
SCR-5500FHZ	Zinc	#5 x 1/2"	25,000
SCR-5625FHZ	Zinc	#5 x 5/8"	20,000
SCR-6500FHZ	Zinc	#6 x 1/2"	20,000
SCR-6625FHZ	Zinc	#6 x 5/8"	15,000
SCR-8625FHZ	Zinc	#8 x 5/8"	12,000
SCR-8750FHZ	Zinc	#8 x 3/4"	10,000
SCR-1625FHZ	Zinc	#10 x 5/8"	10,000
SCR-1750FHZ	Zinc	#10 x 3/4"	8,000
SCR-5500FHB	Black	#5 x 1/2"	25,000
SCR-5625FHB	Black	#5 x 5/8"	20,000
SCR-6500FHB	Black	#6 x 1/2"	20,000
SCR-6625FHB	Black	#6 x 5/8"	15,000
SCR-8625FHB	Black	#8 x 5/8"	12,000
SCR-8750FHB	Black	#8 x 3/4"	10,000
SCR-1625FHB	Black	#10 x 5/8"	10,000
SCR-1750FHB	Black	#10 x 3/4"	8.000

PART#	FINISH	SIZE	BULK CTN QTY.
SCR-6500PHZ	Zinc	#6 x 1/2"	20,000
SCR-6625PHZ	Zinc	#6 x 5/8"	15,000
SCR-6100PHZ	Zinc	#6 x 1"	10,000
SCR-8500PHZ	Zinc	#8 x 1/2"	15,000
SCR-8625PHZ	Zinc	#8 x 5/8"	12,000
SCR-8750PHZ	Zinc	#8 x 3/4"	10,000
SCR-8100PHZ	Zinc	#8 x 1"	8,000
SCR-1625PHZ	Zinc	#10 x 5/8"	10,000
SCR-1750PHZ	Zinc	#10 x 3/4"	8,000
SCR-1875PHZ	Zinc	#10 x 7/8"	7,000
SCR-1100PHZ	Zinc	#10 x 1"	6,000
SCR-6500PHB	Black	#6 x 1/2"	20,000
SCR-6625PHB	Black	#6 x 5/8"	15,000
SCR-6100PHB	Black	#6 x 1"	10,000
SCR-8500PHB	Black	#8 x 1/2"	15,000
SCR-8625PHB	Black	#8 x 5/8"	12,000
SCR-8750PHB	Black	#8 x 3/4"	10,000
SCR-8100PHB	Black	#8 x 1"	8,000
SCR-1625PHB	Black	#10 x 5/8"	10,000
SCR-1750PHB	Black	#10 x 3/4"	8,000
SCR-1875PHB	Black	#10 x 7/8"	7,000
SCR-1100PHB	Black	#10 x 1"	6,000

FINISHING WASHERS

COLOR: NATURAL NYLON



	SCREW	ID		C	D	H	1
PART#	SIZE	IN.	MM	IN.	MM	IN.	MM
CFW-6	6	.143	3.63	.437	11.10	.100	2.54
CFW-8	8	.171	4.34	.515	13.08	.115	2.92
CFW-10	10	.191	4.85	.580	14.73	.152	3.86



FURNITURE ASSEMBLY FASTENERS



POSI SCREWS

Titus

• 250 PIECES PER CARTON •

PART#	DESCRIPTION
OP-0071	8x33mm HI-LO Funnel Head
OP-0077	8x45mm HI-LO Funnel Head
OP-6077	8x50mm HI-LO Funnel Head
OP-6080	11x50mm HI-LO Funnel Head

ANCHORING SOLUTIONS BY TOGGLER®

MADE IN THE U.S.A.

Fast, easy, secure anchoring in ALL building materials — drywall, gypsumboard, brick, concrete, block, stone, plaster ... · No special tools needed

Lowest in-place anchoring cost

Stronger than any anchor of comparable screw size





TOGGLER® BRAND SnapSkru® Self-Drilling Drywall Anchors

- Holds over 80% more than other self-drilling drywall anchors
- Works with #6, #8, and #10 screws (#8 preferred)
- Locks on wall resists shock & vibration
- Positive "stop" resists overturning
 Installs with screwdriver or screw gun
- · Can remove screw & item, leaving anchor in wall for reuse
- Activates with audible "pop", indicating correct installation


PART#	DESCRIPTION	GRIP	SCREW	SCREWS	BOX
TA-0012	SP™ drywall anchors	3/8"-5/8"	#6-#10	50	50

****#8 x 1 1/2" COMBO HEAD SCREWS INCLUDED IN TA-0012 BOXES - EACH ITEM IS SOLD IN FULL BOXES ONLY - NO BROKEN BOXES****

TB®

Walls &

Ceilinas



Securely hang alarms, mirrors, bathroom accessories, picture frames, drapery, lighting fixtures, smoke detectors, thermostats, electric boxes etc.


TOGGLER® BRAND SNAPTOGGLE® Toggle Bolts

Strongest holding in smallest hole • Vibration-proof—anchor centers bolt Can be used with a screw gun—won't spin in the hole • Fast & easy Reusable in same hole—metal channel stays in place when bolt removed

BA 3/16"-24 • BB 1/4"-20 = Drill diameter: 1/2" (13mm) Grip Range: 3/8"-3 5/8" (10mm-92mm) Minimum clearance behind wall: 1 7/8" (48mm)

> BC 3/8"-16 • BD 1/2"-13 = Drill diameter: 3/4" (19mm) Grip Range: 3/8"—2 1/2" (10mm—64mm) Minimum clearance behind wall: 1 7/8" (48mm)

Superior holding for heavy-duty anchoring in hollow walls and ceilings Use in drywall, concrete block, plaster, tile over drywall, or tile over greenboard




	PART#	DESCRIPTION	THREAD	DRILL	GRIP	BOX
T	A-1013	BA™ SNAPTOGGLE toggle bolt	3/16"-24	1/2"	3/8" - 3-5/8"	100
T	A-1014	BB™ SNAPTOGGLE toggle bolt	1/4"-20	1/2"	3/8" - 3-5/8"	100
T	A-1015	BC™ TOGGLER toggle bolt	3/8"-16	3/4"	3/8" - 2-1/2"	25
T	A-1016	BD™ TOGGLER toggle bolt	1/2"-13	3/4"	3/8" - 2-1/2"	25

*****THREADED BOLTS ARE NOT INCLUDED— EACH ITEM IS SOLD IN FULL BOXES ONLY — NO BROKEN BOXES*****

TOGGLER® Hollow-Wall Anchors

Largest range of screw sizes per anchor • Vibration- & shock-proof 5/16" drill only • Can be used with a screw gun • Don't spin in the hole




PART #	DESCRIPTION	GRIP	SCREW	DRILL	BOX
TA-1009	TA® hollow door anchors	1/8"-1/4"	#8-#12	5/16"	100
TA-1010	TB® drywall anchors	3/8"-1/2"	#6-#14	5/16"	100
TA-1011	TC® drywall anchors	5/8"-3/4"	#6-#14	5/16"	100
TA-1021	TD™ drywall anchors	1"	#6-#14	5/16"	50
TA-1029	T35™ drywall anchors	1 3/8"	#6-#14	5/16"	50

*****EACH ITEM COMES WITH 3 SETTING KEYS PER BOX — EACH ITEM IS SOLD IN FULL BOXES ONLY — NO BROKEN BOXES*****

TOGGLER brand anchors are patented under one or more U.S. Patent Nos. 4,673,150; 4,878,790; 4,993,901; 5,028,186; 5,161,296; 5,983,385; 6,161,999; and foreign counterparts thereof and of 4,650,386 and 4,752,170. Other patents pending, TOGGLER and typelace, TA, TB, TC, TH, SnapSkru, SNAPTOGGLE, ALLIGATOR, and ALLIGATOR symbol are worldwide registered trademarks of Mechanical Plastics Corp. A5, AF5, A6, AF6, A8, AF8, BA, BB, BC, BD, SP, TD, T35, and TBS1 are worldwide trademarks of MPC.

TOGGLER® BRAND ALLIGATOR® Solid-Wall Anchors

Outhold metal anchors twice the screw size • Vibration- and shock-proof Corrosion-proof when used with a stainless steel screw . Set instantly Can be used with a screw gun . Don't spin or countersink in the hole



The most modern, versatile, and effective anchor for light to heavy-duty anchoring in solid walls, which also works if you hit a hidden cavity

A series = Flushmount For through-the-fixture anchoring


Anchor extrudes down screw-up to 2x its original length—for high holding values. Anti-rotation fins prevent spinning.

Hollow Anchor also works if it hits a hidden cavity or hollow in or behind the wall Screw thread locks into anchor's teeth

ПП

AF series = Flanged Use where there may be a hollow


Flanged anchors give outstanding holding in tile over drywall & in tile over greenboard



PART #	DESCRIPTION	SCREW	DRILL	вох
TA-3103	AF™ 3/16" dia. flanged anchors	#4-#10	3/16"	200
TA-3101	AF6™ 1/4" dia. flanged anchors	#6-#14	1/4"	100
TA-3102	AF8™ 5/16" dia. flanged anchors	#6-5/16"	5/16"	100
TA-3106	A5™ 3/16" dia. flushmount anchors	#4-#10	3/16"	200
TA-3104	A6™ 1/4" dia. flushmount anchors	#6-#14	1/4"	100
TA-3105	A8™ 5/16" dia. flushmount anchors	#6-5/16"	5/16"	100

****EACH ITEM IS SOLD IN FULL BOXES ONLY — NO BROKEN BOXES*****


TOGGLER® Specialty Anchors



string TV cable or phone wire.

on hollow or solid walls. Also used to

The same vibration- and shock-proof holding of the TOGGLER Hollow-Wall Anchors plus specially designed heads for specialized applications TBS1



installing C-channel wall standards in perfect alignment and preventing jackout of the anchor.

PART #	DESCRIPTION	GRIP	SCREW	DRILL	BOX	
TA-1012	TH® picture hook anchors	3/8"-1/2"	#6-#14	5/16"	100	
TA-1023	TBS1™ shelving anchors	3/8"-1/2"	#6-#14	5/16"	50	
TA-1022	TBS2™pegboard anchors	3/8"-1/2"	#6-#14	5/16"	50	
TA-1024	TBW™ wire shelf anchors	3/8"-1/2"	#6-#14	5/16"	50	
*****EACH ITEM COMES WITH 2 SETTING KEYS DED BOY						

EACH ITEM IS SOLD IN FULL BOXES ONLY — NO BROKEN BOXES*****

ECONOMY WALL ANCHORS



POLYPROPYLENE

Used for through the fixture mounting 1/4" Diameter Flush Mount Anchor

PART# SCREW DRILL STD-ANCHOR #6-#14 1/4"

SOLD IN BOXES OF 100 PCS. - NO BROKEN BOXES

TABLE ESSENTIALS

TABLE ALIGNERS

Material: H.D.P.E.



PART # COLOR CN-01 Brown

#8 Flathead Screws

PART # FINISH SIZE
SCR-8625FHZ Zinc #8 x 5/8"

TABLE PINS

Material: H.D.P.E.


- Self-lubricating for easy, smooth action; will not swell, shrink, check or rust
- No glue required
- Finishing materials will not adhere to the pin; will not mar fine table surfaces
- Table pins are also used for top & bottom glides for sliding doors





PART # COLOR R25-81BE Beige

Material: Steel



#10 Panhead Screws

 PART #
 FINISH
 SIZE


 SCR-1625PHZ
 Zinc
 #10 x 5/8"

DROP LEAF TABLE WEDGE

Material: H.D.P.E.

- Use where sliding surfaces must be protected against friction & wear
- Will not crack or splitStaple under table top





PART # COLOR R50-108DB Dk. Brown

FLIP BOLT CONNECTOR

Material: Steel

Nirvana... the tool-less counter top connector is here.

The Flip Bolt is fast and easy, requires **no tools** and is great for most countertop connections.





PART # SIZE FC-FB 4-1/2"



Reasonable sample quantities are available at no charge for many of the featured products within this catalog to test their suitability for your intended use or application. Please discuss with our sales representatives.

Most samples are sent mail or U.P.S. ground. Next day delivery is available, provided the customer pays the freight.

SWIVELS

7" FLAT OR 3-D

THIS IS OUR MOST POPULAR AND VARIED LINE OF SWIVELS.

7" SQUARE PLATES HAVE SLOTS ON 5-1/4" CENTERS. 12 GAUGE STEEL. PITCH AVAILABLE IN FLAT, 3°.

NOTE: FLAT SWIVELS ARE FOR CHAIRS WITHOUT BACKS, 3-D SWIVELS ARE FOR CHAIRS WITH BACKS.

Top & Bottom Plates, 5-1/4" Slotted Centers 7 Square Plate 12 Gauge Steel Pieces Per Carton: 16



Standard Swivel Used On Entire Trendler Pedestal Base Line. May Be Used In Conjunction With 3-1/4" Weld Plates. Four 1/4"-20 Threaded Holes On 2-1/2" Centers.

Pieces Per Carton: 25 Weight Each: 2.50 Lbs.



REVOLVING TURNTABLES

STEEL LAZY SUSAN

- •Only 5/16" Thick (Can be recessed into surfaces for 1/8" thickness).
- Large, Full Ball Race For Maximum Stability & Smooth Gliding Rotation.
- •360° Interlock Prevents Separation.
- Electro Zinc Coated For Rust Resistance.
- Made in the USA.

		CENTER	WEIGHT	APPROX.	CARTON
PART #	SIZE	HOLE DIA.	CAPACITY	TOP DIA.	QUANTITY
S8-300C	3" Sq.	1-1/4"	200 lbs.	Up to 18"	100
S8-400C	4" Sq.	2-5/32"	300 lbs.	12" - 25"	100
S8-600C	6" Sq.	4-11/16"	500 lbs.	15" - 30"	100
S8-900C	9" Dia.	4-1/2"	700 lbs.	17" - 35"	25
S8-1200C	12" Dia.	6-9/32"	1000 lbs.	20" & Over	25



For Larger Applications

ALUMINUM LAZY SUSAN

SOLID ALUMINUM BALL BEARING SWIVELS CONTAIN LOCK SCREW FOR STATIONARY APPLICATION OR FOR SHIPPING

		WEIGHT
PART#	SIZE	CAPACITY
S8-1300C	13" Dia.	220 lbs.
S8-1600C	16" Dia.	250 lbs.
S8-1800C	17-3/8" Dia.	330 lbs.
S8-2400C	24" Dia.	700 lbs.



*Nonskid feet on upper & lower rail. Drill holes on upper & lower rail.



3M™ HOT MELT BONDING SYSTEMS







HELP YOU IMPROVE PRODUCTIVITY, LOWER COST & MINIMIZE WASTE

Our new, lightweight, easy-to-use Polygun™ Applicators use Jet-melt™ Adhesives for fast,strong bonds on a variety of surfaces - wood, plastic, foam, fabric, cardboard, rubber and more. (TECHNICAL INFO AVAILABLE UPON REQUEST)

Jet-melt™ Adhesives

SIZE

5/8" x 2'

5/8" x 8"

5/8" x 2"

5/8" x 8"

5/8" x 2"

5/8" x 2"

5/8" x 8"

STICK

SIZE

5/8" x 8"

COLOR

Tan

Off White

Tan

Tan

Clear

Clear

Clear

COLOR

Lt. Amber

Clear

PART# WEIGHT

11 lbs.

3792-LM-Q 11 lbs. 5/8" x 8"

BOX

WEIGHT

3738

3748-Q

3762

3762-Q

3764

3792

3792-Q

PART#

3762-LM-Q 11 lbs.

HIGH

TEMP

GLUE

STICKS

HEAT

RESISTANCE

130°

175°

130°

130°

140°

140°

140°

HEAT

RESISTANCE

130°

140°

POLYGUN™ APPLICATORS

120 VOLT/150 WATT

HIGH TEMPERATURE APPLICATORS

Deliver up to 3.5 lbs. of adhesive per hour at 385°F

PART # DESCRIPTION

PGTC-Q Standard Gun w/Quadrack & Palm Trigger

MULTIPLE TEMPERATURE APPLICATOR

Deliver up to 2.6 to 5.5 lbs. of adhesive per hour at 26.-450°F
PART # DESCRIPTION

PGEC Multiple Temperature Gun

Provides multiple temperatures with choice of preset temperature module kits that insert into the handle. Capable of dispensing new low melt Jet-melt™ adhesives.

LOW TEMPERATURE GLUE STICKS

PART # FEATURES/APPLICATION IDEAS

3762-LM Improved "hot tack" when dispensed at low melt temperature. Can bond beadboard, corrugated, displays.

PART#

GLUE

STICKS

FEATURES/APPLICATION IDEAS

3792-LM Clear Long bonding range when dispensed at low melt temperature. Can bond woods, P.O.P. displays, corrugated, polyolefins and other lightweight materials.

HIGH TEMPERATURE GLUE STICKS

PART#	FEATURES/APPLICATION IDEAS
3738	High delivery and long bonding range. General
Tan	purpose for foundry sand cores, exhibits, wood
Tall	bonding, corrugated and chipboard.
3748	Good thermal and electrical properties. Non-
Off	corrosive to copper. Can bond polypropylene,
White	polyethylene.

PART#

Clear

FEATURES/APPLICATION IDEAS

3762 Tan Excellent "hot tack", fast-setting for corrugated packaging, recouperage, repacking area, warehouse. Low cost, general purpose. Can bond chipboard, wood.
 3764 Clear Clea

Can bond fabric and other lightweight materials.

3M™ FLEXIBLE ADHESIVES

3MTM

Scotch-Grip[™] and Fastbond[™] brand adhesives are industrial-quality products designed to provide innovative answers to a wide variety of non-structural bonding problems. Some formulations are tailored to specific types of applications; while others are multipurpose and used worldwide in hundreds of different product assembly operations. (TECHNICAL INFO AVAILABLE UPON REQUEST)

30 NF FASTBOND™ CONTACT ADHESIVE, GREEN (PROTECT FROM FREEZING)

A water dispersed high strength contact adhesive that changes color from blue to green when dry. Has high coverage, a long bonding range and good heat resistance. Can be used to bond foamed plastics, plastic laminate, wood, plywood and wood veneer, and canvas to themselves and each other, as well as for postforming operations. Meets requirements of MIL-A-24179-A.Non-flammable in the wet state.

		CASE
PART#	SIZE	QUANTITY
4276-Q	Quart	12
4276-G	Gallon	4
4276-P	5 Gallon Pail	-

30 NF FASTBOND™ CONTACT ADHESIVE, CLEAR (PROTECT FROM FREEZING)

A water dispersed high strength contact adhesive that has high coverage, a long bonding range and good heat resistance. Can be used to bond foamed plastics, plastic laminate, wood, plywood and wood veneer, and canvas to themselves and each other, as well as for postforming operations. Meets requirements of MIL-A-24179-A. Non-flammable in the wet state.

		CASE
PART#	SIZE	QUANTITY
4274-Q	Quart	12
4274-G	Gallon	4

STA'-PUT ADHESIVES

MULTI-PURPOSE SPRAY ADHESIVE SYSTEM

STA'-PUT SPH

Colors: Clear & Red

STA'-PUT spray adhesive has been formulated to provide excellent adhesion over awide range of product applications; securing duct liner, securing duct wrap, board lamination, laminates to laminates, sealing vapor barrier, M.B.I. repair, fire proofing base coat, sealing flex foam, building insulation blocks for a pipe covering operation, mitering fittings & ASJ, FSK, aluminum, PVC to all pipe insulations.

- NON-FLAMMABLE
- · EASY CLEAN UP
- COMPLETELY PORTABLE
- · DRIES CLEAR
- · NO CLOGGED TIPS
- · WATER RESISTANT
- · GUARANTEED SHELF LIFE
- · HIGH TACK
- NO FLASHING REQUIRED
- · QUICK SETTING

SPRAY ADHESIVE

PART #	DESCRIPTION	COLOR
SAS-45	15 oz. Can	Clear
SAS-45-R	15 oz. Can	Red
SAS-50	11 lb. Canister	Clear
SAS-50-R	11 lb. Canister	Red
SAS-51	37 lb. Canister	Clear
SAS-51-R	37 lb. Canister	Red

STA'-PUT SPH LIQUID

LIQUID ADHESIVE

PART # DESCRIPTION COLOR
SAS-70 5 Gallon Drum Clear

STA'-PUT II has been specifically formulated to provide permanent bonding of Styrofoam and all other polystyrene materials with no adverse reaction to the bonded surfaces. Requires 4 minutes to set and bond. Firm pressure is required only during the immediate bonding process.

STA'-PUT II

Colors: Clear & Blue

SPRAY ADHESIVE

PART#	DESCRIPTION	COLOR
SAS-65	13 oz. Can	Clear
SAS-66	30 lb. Canister	Clear
SAS-66-BL	30 lb. Canister	Blue

SP-80 GREEN ADHESIVE

Solvent based, low VOC, non-chlorinated contact adhesive certified for many industry standards



SPRAY ADHESIVE

PART#	DESCRIPTION	COLOR
SP-80-14	14 oz. Spray Can	Clear
SP-80-27	27 lb. Canister	Clear

LIQUID ADHESIVE

PART#	DESCRIPTION	COLOR
SP-80-5	5 gal. Pail Drum	Clear







STA'-PUT SPH/II REMOVER

PART # DESCRIPTION SAS-46 15 oz. Can

PLEASE NOTE: STA'-PUT ADHESIVES CAN ONLY BE SHIPPED VIA RPS!

DOUBLE COATED ADHESIVE TAPES

3MTM

High-strength Scotch™ VHB tapes are used throughout the industry today to replace screws, rivets, welding, liquid adhesives and other permanent assembly methods. They offer greater design flexibility and are often the key to dramatic improvements in styling and performance. Moreover, they allow faster, easier assembly, eliminate cleanup & increase profits. (TECHNICAL INFO AVAILABLE UPON REQUEST)

3M™ BRAND VHB™ HIGH STRENGTH ACRYLIC FOAM TAPE

Clear, closed cell acrylic foam carrier - excellent for joining transparent materials.

PART #	THICKNESS	WIDTH	ROLL SIZE	CASE QUANTITY
4905-0500		1/2"	72	18
4905-0750	.020	3/4"	72 Yds	12
4905-1000		1"	rus.	9
4910-0500		1/2"	26	18
4910-0750	.040	3/4"	36 Yds	12
4910-1000		1"	rus.	9

Very conformable black closed cell acrylic foam tape 45 mill thick, PE liner.

PART#	ROLL SIZE	CASE QUANTITY
5952-0500	36 Yds.	18
5952-0750	15 Yds.	12
5952-1000	36 Vds	g

Very conformable gray closed cell acrylic foam tape 45 mill thick, paper liner.

	CASE
PART #	QUANTITY
4941-0500	18
4941-0750	12
4941-1000	9

White, closed cell acrylic foam carrier - features an all-purpose adhesive.

PART#	THICKNESS	WIDTH	ROLL	CASE QUANTITY
4930-0500		1/2"		18
4930-0750	.025	3/4"	72 Yds.	12
4930-1000		1"	rus.	9
4950-0500		1/2"	36	18
4950-0750	.045	3/4"	Yds.	12
4950-1000		1"	Tus.	9

3M™ RUBBER-BASED POLYETHYLENE FOAM TAPE

*Available in Black or White

PART#	THICKNESS	WIDTH	ROLL SIZE	CASE QUANTITY
4462-0500*		1/2"	72	18
4462-0750*	.030	3/4"	Yds.	12
4462-1000*		1"	rus.	9

PART #	THICKNESS	WIDTH	ROLL SIZE	CASE QUANTITY
4466-0500*		1/2"	36	18
4466-0750*	.060	3/4"	Yds.	12
4466-1000*		4"	rus.	a

PLEASE NOTE: ABOVE TAPES ARE STOCK ITEMS.

OTHER SCOTCH™ BRAND ADHESIVE TAPES ARE AVAILABLE PLEASE INQUIRE FOR LEAD TIMES

RUBBER-BASED DOUBLE COATED ADHESIVE TAPES

POLYETHYLENE FOAM TAPE

ROLLS

Available 1/32" or 1/16" thick
- 1/2", 3/4" or 1" Wide
- White or Black
- 216 Ft. Rolls



1/32" THICK

PART #	WIDTH	PER CASE
RFT1-0500-	1/2"	24
RFT1-0750-	3/4"	16
RFT1-1000-	1"	12

1/16" THICK

		ROLLS
		PER
PART #	WIDTH	CASE
RFT2-0500-WH	1/2"	24
RFT2-0750-WH	3/4"	16
RFT2-1000-WH	1"	12

DOTS

Available 1/32" or 1/16" thick - 1/2", 3/4" or 1" Wide - White Only



1/32" THICK

PART#	DIA.
RFT1-120	1/2"
RFT1-340	3/4"
RFT1-100	1"

1/16" THICK

PART#	DIA.
RFT2-120	1/2"
RFT2-340	3/4"
RFT2-100	1"

CLEAR FILM TAPE

- .5mil polyester film with 2mil adhesive
- Rubber based adhesive not recommended for direct UV exposure applications
- · Application temperature: 65°F-100°F
- Service temperature: -20°F-150°F
- · Roll core: 3" Diameter -180 Ft.



PART #
DK-0500
DK-0750
DK-1000

BINNING STRIPS



OUR BINNING STRIP MAKES IT EASY TO ADJUST SPACING & ACCOMMODATE YOUR NEEDS

Material: Ivory, White, Black & Clear Styrene


Versatile plastic band strip can be installed on counters, tables, cabinets, in drawers anywhere. Accepts various types of dividers. Economical yet easily installed.



STANDARD BABY BINNING STRIP

FOR 1/4" DIVIDER

Works independently of standard binning strip





1	1/8"	1	\mathbf{H}	H
1	1/8"	Н		H
	1/8"			

PART #	DESCRIPTION
292-BK-60	60"-Black-No adhesive
292-CL-60	60"-Clear-No adhesive
292-IV-60	60"-Ivory-No adhesive
292-WH-60	60"-White-No adhesive
292A-BK-60	60"-Black-w/adhesive
292A-CL-60	60"-Clear-w/adhesive
292A-IV-60	60"-Ivory-w/adhesive
292A-WH-60	60"-White-w/adhesive

STANDARD BINNING STRIP

FOR 1/4" DIVIDER







PART#	DESCRIPTION
282-CL-48	48"-Clear-No adhesive
282-CL-60	60"-Clear-No adhesive
282-IV-48	48"-Ivory-No adhesive
282-IV-60	60"-Ivory-No adhesive
282-WH-48	48"-White-No adhesive
282-WH-60	60"-White-No adhesive
282-BK-60	60"-Black-No adhesive
282A-CL-48	48"-Clear-w/adhesive
282A-CL-60	60"-Clear-w/adhesive
282A-IV-48	48"-Ivory-w/adhesive
282A-IV-60	60"-Ivory-w/adhesive
282A-WH-48	48"-White-w/adhesive
282A-BK-48	48"-Black-w/adhesive
282A-WH-60	60"-White-w/adhesive
282A-BK-60	60"-Black-w/adhesive

STANDARD BINNING STRIP

FOR 1/8" DIVIDER





PART#	DESCRIPTION
182-CL-60	60"-Clear-No adhesive
182-IV-60	60"-Ivory-No adhesive
182-WH-60	60"-White-No adhesive
182-BK-60	60"-Black-No adhesive
182A-CL-60	60"-Clear-w/adhesive
182A-IV-60	60"-Ivory-w/adhesive
182A-WH-60	60"-White-w/adhesive
182A-RK-60	60"-Black-w/adhesive

DRAWER ESSENTIALS


SOLID BIRCH DRAWER PARTS

Material: Solid Birch Drawer Construction Components with Clear Catalyzed Finish (Natural Light)

Sides and fronts/backs are 5/8" solid edge glued birch components. Straight and true, our drawer components are finished with a durable UV coating and available in 6 sizes for any drawer application. Side lengths are 22" (558.8mm) and fronts/backs are 96" (2438.4mm).

Drawer bottoms are also available in 5mm Birch Plywood (BIBB grade).







DRAWER SIDES

	PART#	HEIGHT	LENGTH	BOX QTY.	
Ī	DS-2-BIR	2-1/2"	22"	20 pcs.	
	DS-3-BIR	3-1/2"	22"	20 pcs.	
	DS-4-BIR	4"	22"	20 pcs.	
	DS-6-BIR	6"	22"	20 pcs.	
	DS-8-BIR	8"	22"	10 pcs.	
	DS-10-BIR	10"	22"	10 pcs.	
	* DS-10-BIR-NG	10"	22"	10 pcs.	

^{*} Products with an NG part number are supplied with no groove and have a finished radius on both sides for custom heights.

DRAWER FRONTS/BACKS

PART #	HEIGHT	LENGTH	BOX QTY.
DF-2-BIR-8	2-1/2"	96"	5 pcs.
DF-3-BIR-8	3-1/2"	96"	5 pcs.
DF-4-BIR-8	4"	96"	5 pcs.
DF-6-BIR-8	6"	96"	5 pcs.
DF-8-BIR-8	8"	96"	3 pcs.
DF-10-BIR-8	10"	96"	3 pcs.
*DF-10-BIR-NG-8	10"	96"	3 pcs.

^{*} Products with an NG part number are supplied with no groove and have a square edge on both sides for custom heights.



DRAWER BOTTOM


PART #	HEIGHT	LENGTH	BOX QTY.
DB-2160	21-7/8"	60"	3 pcs.

Ends can be joined by gluing, nailing or cutting out dovetail joinery.

RUNNER WHEEL

Material: Nylon

- · Simple Cost Effective · Eliminates need for drawer slides



11mm drilled hole

DRAWER FRONT ADJUSTER

Material: Nylon

Use on drawer fronts to provide realignment facility on fronts attached to 4-sided drawers. Housing is nylon with die cast threaded insert screw. plated steel. Housing is hammer driven into a 25MM prebored hole. Screw attaches 4th side of drawer to allow adjustment of front until fully tightened. Screw size is 7/8" x 8/32". Features: 2mm of adjustment in vertical or horizontal directions. 25mm hole boring in drawer front. Large head screw attachment to 4th side of drawer. Simple to use.




DRAWER ESSENTIALS

DRAWER DIVIDERS

Material: Clear Polycarbonate



· Can be screw mounted or applied with adhesive



PART #	COLOR	DESCRIPTION
R83-941CL	Clear	Screw Mount
R83-941CL-A	Clear w/Adh	Adhesive




FLEXA-TOUCH®

Material: Natural ABS

- · Designed to allow drawers to be opened just by pushing on the front
- Adjust for flush alignment from 7/8" to 3" max

Screws included

PART# OI-1021



DRAWER BUMPERS




· Put bumpers on drawers to prevent damage to cabinet doors



PART#	COLOR	THICKNESS
R51-DB51-WH	White	29/64" (11.5mm)
R51-DB51-BE	Beige	29/64" (11.5mm)
R51-DB18-WH	White	23/32" (18mm)
R51-DB18-BE	Beige	23/32" (18mm)

UNDERMOUNT ROLLOUT BUMPERS





· When used, will prevent damage to cabinet doors




PART #	COLOR
R51-C47-WH	White
R51-C47-BF	Beige

DRAWER DIVIDER CLIPS

Material: Delrin

· Spring action design will securely hold divider panels up to 1/4" thick



PART #	COLOR	LENGTH
R83-6200-BK	Black	2-3/8" L
R83-6230-BK	Black	3-5/8" I

Corner Braces can be found on page 286

DRAWER DIVIDER SUPPORTS

Material: Polvethylene

- Groove type for 1/4" 5/16" drawer dividers
- · Supports are installed in grooves in drawer side.
- Divider may be adjusted by removing it and relocating the supports.







PART# COLOR R83-190BE Beige


REMOVABLE DRAWER OUTSTOP

Material: Polypropylene

· Mount on back of drawer to prevent from pulling out

DOVETAILS / DRAWERS

 Tip out stop forward to remove & upon reinsertion merely push the drawer all the way in & it will automatically snap into place





PART#	COLOR	Α	В
R51-423BE	Beige	1-3/4"	3/4"
R51-424BE	Beige	2"	1"
R51-468BE	Beige	1-3/8"	3/8"


SCREW PART # SCR-6500FHZ #6 x 1/2" Flat Head Zinc

FALSE DRAWER FRONT CLIPS



- · Used to attach finished fronts to cabinet that will have limited use
- · Also, ideal for access panels that must be removable yet secure
- Use #6 screw x 1/2" (sold separately below)

Material: ABS False Front Clip for 4-1/2" Opening






COLOR PART# FFDC-30 Natural

Material: Polycarbonate

False Front Clip with 1" Mounting Plate



FFDC-10







SCREW PART # SCR-6500PHZ


#6 x 1/2" Flat Head Zinc


DRAWER ESSENTIALS


Cut-Program Available
SEE PAGE 29 FOR DETAILS


PLASTIC HANGING FILE FOLDER MOULDINGS


LENGTHS: 8 FT.













FILE BAR HOLDERS

Material: Black Acetate

• Fits Up To 1/2" Thick Drawer Sides

• Holds 1/8" x 1/2" File Bar



PART #	DESCRIPTION	DIMENSIONS
R83-6100-BK	Hanging File Bar Holder	1-1/8" H x 15/16" W
R83-6120-BK	Screw Mount File Bar Holder	1-5/8" H x 1/2" W
R83-6130-BK	90° File Bar Holder	7/16" H x 15/16" W

PENDA FLEX BAR

RECTANGULAR BAR

Material: Aluminum • Lengths: 8 Ft.

Finishes Available

*M - Mill - Dull Finish: As Extruded -

May or May Not Have "Scratches"/Die Lines

*BK - Black - Powder Coated



	PART #	Α	В	Length	Mill	Black
	ALU599-18-*	1/2"	1/8"	120 Ft.		
				600 Ft.		
New	¥ ALU600-18-*	3/4"	1/8"	120 Ft.		
TO V				600 Ft.		

LOCKS

BASIC CAM

MINIATURE TUBULAR PUSH LOCK





PART #
RA713-CHR-KA

- Material: Zinc Alloy
- · Chrome plated finish
- Size: 3/8" L x 7/16" Diameter
- Drawer Thickness: 1/4"
- Keyed alike only
- · Comes with 2 keys

160 P

PART #
RA709-CHR-KA

CAM LOCK

- Material: Metal construction
- · Chrome plated finish
- Size: 7/8"
- Drawer Thickness: Up to 5/8" panel
- Keyed alike only

Spare Keys for RA709-CHR-KA #KY-135...set of two

DRAWER LOCKS

SLIDING GLASS SHOWCASE DRAWER LOCK



RA710-CHR-KA

- Material: Metal construction
- · Chrome plated finish
- Size: 5-1/2" Ratchet bar
- Drawer Thickness: From 3/16" to 1/4" glass panel
- Keyed alike only

Spare Keys for RA710-CHR-KA #KY-035...set of two

PART#

RA711-CHR-KA

SCREW PART # SCR-6625PHZ

#6 x 5/8" Pan Head Zinc

DRAWER LOCK

- Material: Metal construction
- · Chrome plated finish
- Size: 2-1/2" W x 1-1/2" H
- Drawer Thickness: 7/8"
- Keyed alike only

Spare Keys for RA711-CHR-KA #KY-101...set of two

LOCKS

DRAWER LOCK

For Wooden Doors







Material: Zinc Alloy

Nickel finish

• Size: DL-50711: 1-1/2" x 1-1/2" x 1/4" thick DL-50822: 1-1/2" x 2" x 1/4" thick

• Drawer Thickness: 20mm wooden drawer

· Keyed alike only

• Comes with 2 keys

• Use #5 wood screws, (Not included)

PART# SIZE DL-50711-CHR 1-1/2" x 1-1/2" DL-50822-CHR 1-1/2" x 2"

DRAWER LOCKS

PUSH LOCK

For Sliding Cabinet Doors



- · Material: Zinc Die Cast
- · Polished Chrome finish
- · Size: 7/8" Depth
- · Keyed alike only
- · Comes with screws and cup strike

PART# PL-10

SCREW PART # SCR-6625PHZ

#6 x 5/8" Pan Head Zinc

PUSH LOCK

For Wooden Drawers





- · Material: Zinc Alloy
- Size: 3/4" Hole required, overall 3/4" x 2"
- Drawer Thickness: 5/8" 3/4"
- Keved alike only
- · Comes with 2 keys
- Use #5 wood screws, (Not included)

PART #	COLOR/FINISH		
PL-604-BK	Black		
PL-604-CHR	Chrome		

PADLOCKABLE CAM LOCK



- Material: Zinc Alloy
- Size: 1.31" Cylinder length, 3/4" Diameter
- Drawer Thickness: Up to 7/8"
- · Built in finger pull

PART# **FINISH** GL-7840D-BK Matte Black GL-7840D-CHR Chrome

LOCK AIDS ECONOMY PADLOCKABLE CAM LOCK



- Material: Zinc Alloy
- · Chrome finish
- Size: 1-1/8" Cylinder length, 3/4" Diameter
- Drawer Thickness: Up to 7/8"

COMBINES CAM LOCK WITH FLEXIBILITY OF A PADLOCK

PART# GL-7840E-CHR

BLACK THUMB TURN NO **CAM LOCK**




- Material: Zinc Alloy
- · Black/Chrome finish
- Size: 5/8" L x 3/4" Diameter
- Drawer Thickness: Up to 3/8"
- Spun on 1-1/8" straight cam, 90° turn


PART# CAM-0742

DECO-HASP

Material: Acrylic DR101 (Clear), ABS (Black)



Innovative locking hasp designed for corner or flat applications. No moving parts reduce breakage in the field. Solvent bonds to acrylic, polycarbonate, ABS and styrene.




DESCRIPTION PART#

DECO-HASP-LCL Clear Acrylic 7/8" L x 3/4" W x 3/4 H Flat Mount Hasp **DECO-HASP-LBK** Black ABS 7/8" L x 3/4" W x 3/4 H Flat Mount Hasp Clear Acrylic 1-3/8" L x 3/4" W x 7/16" H Corner Mount Hasp DECO-HASP-ZCL

DECO-HASP-ZBK Black ABS 1-3/8" L x 3/4" W x 7/16" H Corner Mount Hasp

ACRYLIC HASP

- · Color: Clear, Black or White
- 2-3/8" Long x 1-1/16" Wide x 1/8" Thick



Bottom section of hasp is reversible for either corner or flat mounting. Pre-determine assembly before inserting pin completely!

PART #	COLOR
HSP-110-CL	Clear
HSP-110-BK	Black
HSP-110-WH	White

COMBINATION CAM LOCK



- Material: Zinc Alloy
- · Chrome finish
- Size: 1-1/8" Cylinder
- Drawer Thickness: Up to 7/8"
- Screws included
- Master key override and code discovery

PART# COM-CAM-7432

2 Keys & Change Pin for COM-CAM-7432 #7432-KEYS

COMBINATION LOCKS 4 DIGIT COMBINATION LOCK





- Material: Zinc and Plastic
- Nickel finish
- Size: 4-3/8" x 3-1/8"
- Drawer Thickness: For 1mm - 28mm thick plate
- · Comes with 2 keys
- Screws included

PART# COM-LOK-DL01

COMBINATION RATCHET LOCK





- Material: Zinc Allov
- · Black/Chrome finish
- Size: 5-3/8" Ratchet bar
- Glass Thickness: 1/2" · Master key included

PART#

RA-7860S

PULL OUT PENCIL DRAWER

UNDER THE DESK STORAGE SOLUTIONS

FEATURES	1	2	3	4
Black	~	~	/	1
Silver				1
Contoured Handle for easy access	~			
Centrally located finger tab for easy opening			~	
Designed to fit desks with shorter depth	~	~		
Narrow Width	~			~
Wide Width		~	~	
Pen/Pencil compartments with plastic tray	~	~	~	~
Ball Bearing Slides			~	
Roller Slide with Plastic Tray	~	~		
Screw Mount - Rotates				~
Mounting Hardware	~	~	~	1
Built in Tape Dispenser				~
Made in U.S.A.	~		~	~



PART# PDN-1BK DIMENSIONS: 17.956"L x 12.75"W x 2.34"D














PART# PDR-451-**DIMENSIONS:** 13.625"L x 8.25"W x 1.375"D

*Available in Black (BK) or Silver (SL)

UTILITY TRAYS





R11-82BK Black







ORGANIZER GROMMET





Black Only

PART# **BK8865**



COMPUTER ACCESSORIES

KEYBOARD TRAYS

FEATURES	1	2	3	4
Reversible mouse tray for right or left hand users		~	~	~
Gel wrist rest			~	1
Gel mouse pad			~	~
Pen/pencil storage		/		
Contoured wrist support	~	~		
Fully articulates: swivels and retracts				~
Slides on track				~
Ball bearing slides	~	~	1	
Includes all mounting hardware	~	~	~	~
Made in the U.S.A.	~	1	~	~




PART # COLOR

CT24-BK Black

DIMENSIONS:
18.23"L x 19.95"W x 3.90"D







	PART #	COLOR		
	CT48-BK	Black		
3	DIMENSIONS:			
	18.20"L x 26.38"W	x 3.90"D		



	PART #	COLOR			
	CT-EKS-BK	Black			
4	DIMENSIONS:				
	12.40"L x 26.38"W x 8.53"D (lowest)				



PART # COLOR

NT-894 Black

MATERIAL: Steel
DIMENSIONS:16.03"L x 17.11"W x
2.0625"D

PENCIL & NOTEBOOK DRAWERS

FEATURES	1	2	3	4
Ball bearing slides	/	~	/	~
Lockable	~			
Wrist rest	/			
Wire management slots	~			
Includes all mounting hardware	/	~	~	~
Made in the U.S.A.	~	1	1	~



	1 (1) 1 (1)	COLOR
	PT-897	Black
2	MATERIAL: High DIMENSIONS:19. 1-7/8"D	Impact Polystyrene 19"L x 21.29"W x



PART # COLOR
PT-8931 Black
MATERIAL: High Impact Polystyrene
DIMENSIONS:17.95"L x 12.75"W x
2-3/4"D



PART # COLOR
PT-893 Black

MATERIAL: High Impact Polystyrene
DIMENSIONS:16.25"L x 21.375"W x
1.875"D



PRODUCT FEATURES:

- Material: ABS
- Color: Black
- 1/4" lip area
- Friction fit molded ribs.
- Can be used as a cup holder or a paper clip holder.
- Other colors may be available. Minimums apply - please inquire.





PART # DIAMETER
36BKS 2-13/16"
36BKD 2-13/16"

FULL EXTENSION SOFT CLOSE UNDERMOUNT DRAWER SLIDES

JUST A SLIGHT PULL IS ALL YOU NEED

- Material: Steel with Plastic Mechanisms
- Easily pulls open & closes with the Grass soft-close dampening system.
 - Full extension with synchronized mechanism.
 - Each pair of slides is handed- 1 left & 1 right.
 - For use with up to 5/8" drawer material.



DYNAPRO 2-D STANDARD DUTY FULL EXTENSION SOFT CLOSE DRAWER

FACE FRAME OR FRAMELESS APPLICATION







PRODUCT FEATURES:

- Integrated 2-dimensional adjustment for alignment-height + 3.5 mm & side \pm 1.5 mm
- 100 lb. static load capacity, 88 lb. dynamic load capacity
- Each set includes slides, left & right front fixing brackets, and two rear mount brackets (rear mount brackets required for face frame applications only).

	DRAWER	CABINET	INTERIOR CABINET DEPTH	
PART#	LENGTH	DEPTH	MINIMUM MAXIMU	
OI-DP2D-9	9"	12"	11-15/32"	11-3/4"
OI-DP2D-12	12"	15"	12-7/8"	14-9/16"
OI-DP2D-15	15"	18"	15-7/8"	17-9/16"
OI-DP2D-18	18"	20"	18-27/32"	20-9/16"
OI-DP2D-21	21"	24"	21-27/32"	23-17/32"

DYNAPRO 3-D HEAVY DUTY FULL EXTENSION SOFT CLOSE DRAWER SLIDES







PRODUCT FEATURES:

- For Frameless Application
- Integrated 3-dimensional adjustment for alignmentheight + 3.5 mm, side ± 1.5 mm & tilt + 4.0 mm
- 132 lb. dynamic load capacity
- Each set includes slides, left & right front fixing brackets, and left & right rear adjustment brackets

	DRAWER	NOMINAL	MINIMUM
PART#	LENGTH	LENGTH	CABINET DEPTH
OI-DP3D-18	18"	18-11/16"	18-27/32"
OI-DP3D-21	21"	21-11/16"	21-27/32"
OI-DP3D-24	24"	24-23/32"	24-7/8"
OI-DP3D-27	27"	27-23/32"	27-7/8"
OI-DP3D-30	30"	30-23/32"	30-7/8"

ACCESSORIES

PENINSULA BRACKETS

• Material: ABS Ol-242



REAR UNDERMOUNT INSET SOCKET

• Material: ABS Ol-276



REAR UNDERMOUNT OVERLAY SOCKET

• Material: ABS OI-280



SPACER


• Material: ABS OI-3640




TO CALCULATE OUTSIDE DRAWER WIDTH

Frameless

Face Frame




Calculation Outside Drawer Width						
Drawer side thickness	16 (5/8")	15 (9/16")	14 (9/16")	13 (1/2")		
Deduct from inside cabinet width	10 (3/8")	12 (1/2")	14 (9/16")	16 (5/8")		



Deduct drawer sides width times 2 from inside cabinet width

75 LB. FULL EXTENSION SOFT CLOSE CONCEALED UNDERMOUNT SLIDE



PRODUCT FEATURES:

- Galvanized Steel
- Has great smooth running qualities
- Can be used with Frameless or Face Frame cabinets
- · Easy close device prevents slamming
- Each set includes slides, front mounting clips and rear mounting brackets

		LOAD
PART#	LENGTH	RATING
OI-4100-12	12"	85 lbs.
OI-4100-15	15"	80 lbs.
OI-4100-18	18"	80 lbs.
OI-4100-21	21"	75 lbs.

ACCESSORIES

REAR UNDERMOUNT SOCKET

• Material: ABS OI-680



SPACER

• Material: ABS



MOUNTING SCREWS SOLD SEPARATELY

16 pieces required per pair SCR-6625FHZ



See page 300 for our complete screw line

BINNING STRIP FOR DRAWERS

Material: Ivory, White, Black & Clear Styrene





STANDARD BINNING STRIP FOR 1/4" DIVIDER

STANDARD BABY BINNING STRIP


FOR 1/4" DIVIDER
Works independently of

Works independently of standard binning strip

									-
									-
п	п	ш	п	п	п	п	ш	ю	- 2
									- 2
									2

N T	1		1		T
1	1/8	Н	\vdash	H	-
1 3/4	200	H	\vdash		-
1/1	1/8"	H	H	H	F


PART #	DESCRIPTION
292-BK-60	60"-Black-No adhesive
292-CL-60	60"-Clear-No adhesive
292-IV-60	60"-Ivory-No adhesive
292-WH-60	60"-White-No adhesive
292A-BK-60	60"-Black-w/adhesive
292A-CL-60	60"-Clear-w/adhesive
292A-IV-60	60"-Ivory-w/adhesive
292A-WH-60	60"-White-w/adhesive




PART #	DESCRIPTION
282-CL-48	48"-Clear-No adhesive
282-CL-60	60"-Clear-No adhesive
282-IV-48	48"-Ivory-No adhesive
282-IV-60	60"-Ivory-No adhesive
282-WH-48	48"-White-No adhesive
282-WH-60	60"-White-No adhesive
282-BK-60	60"-Black-No adhesive
282A-CL-48	48"-Clear-w/adhesive
282A-CL-60	60"-Clear-w/adhesive
282A-IV-48	48"-Ivory-w/adhesive
282A-IV-60	60"-Ivory-w/adhesive
282A-WH-48	48"-White-w/adhesive
282A-BK-48	48"-Black-w/adhesive
282A-WH-60	60"-White-w/adhesive
282A-BK-60	60"-Black-w/adhesive

STANDARD BINNING STRIP

FOR 1/8" DIVIDER






PART #	DESCRIPTION
182-CL-60	60"-Clear-No adhesive
182-IV-60	60"-Ivory-No adhesive
182-WH-60	60"-White-No adhesive
182-BK-60	60"-Black-No adhesive
182A-CL-60	60"-Clear-w/adhesive
182A-IV-60	60"-Ivory-w/adhesive
182A-WH-60	60"-White-w/adhesive
182A-BK-60	60"-Black-w/adhesive

100 LB. LOW PROFILE FULL **EXTENSION DRAWER SLIDE**

OI-5043 SERIES





PRO	DUC	T FEA	TURES	•

- Available Lengths: 10"-28"
- Material: Cold rolled steel with steel ball bearings
- Finish: Clear Zinc
- Side mounted with trigger release
- · Low profile for shallow drawers and traditional desks
- Low profile, only 43 mm (1.69" height)
- · 100 lbs. Load Rating
- Full extension travel
- 1/2" side spacing
- Trigger release design
- Face Frame hole
- · 32 mm screw mounting system

PART #	LENGTH	RATING	CARTON SIZE
OI-5043-10	10"	120 lbs.	10 Pairs
OI-5043-12	12"	120 lbs.	10 Pairs
OI-5043-14	14"	115 lbs.	10 Pairs
OI-5043-16	16"	110 lbs.	10 Pairs
OI-5043-18	18"	105 lbs.	10 Pairs
OI-5043-20	20"	100 lbs.	10 Pairs
OI-5043-22	22"	95 lbs.	10 Pairs
OI-5043-24	24"	90 lbs.	10 Pairs

PENINSULA BRACKETS

• Material: Steel & ABS

OI-679

MOUNTING SCREWS SOLD SEPARATELY

16 pieces required per pair

SCR-6625FHZ

See page 300 for our complete screw line

ACCESSORIES

REAR MOUNT METAL SOCKET

• Material: Steel & ABS

OI-5043B-S



SPACER


• Material: ABS **OI-3616**



EASY CLOSE SOFT CLOSE DAMPENING SYSTEM

Works with any drawer slide.







PRODUCT FEATURES:

- · Material: Grey high impact polystyrene
- · 3 models available to accommodate side clearance .39" (10 mm) - .53" (13.5 mm)
- · Drawer is softly dampened & pulled shut without slamming
- · All mounting hardware & installation instructions included

	DRAWER	SIDE	
PART#	WEIGHT	CLEARANCE	PACKING
OI-8002	Up to 40 lbs.*	.39" (10 mm)53" (13.5 mm)	Per Piece
OI-8001	Up to 75 lbs.	.49" (12.5 mm)	Per Pair
OI-8003	Up to 150 lbs.	.49" (12.5 mm)	Per Pair
*NON-HAN	NDED-USE 2 PIECE	S FOR DRAWERS U	P TO 80 I BS.

ECONOMY 100 LB. FULL EXTENSION SLIDE



		LOAD	RECOMMENDED	CARTON
PART #	LENGTH	RATING	DRAWER WIDTH	SIZE
OI-9400-10	10"	120 lbs.	10"	10 Pairs
OI-9400-12	12"	115 lbs.	12"	10 Pairs
OI-9400-14	14"	110 lbs.	14"	10 Pairs
OI-9400-16	16"	105 lbs.	16"	10 Pairs
OI-9400-18	18"	100 lbs.	18"	10 Pairs
OI-9400-20	20"	100 lbs.	20"	10 Pairs
OI-9400-22	22"	100 lbs.	22"	10 Pairs
OI-9400-24	24"	85 lbs.	24"	10 Pairs
OI-9400-26	26"	80 lbs.	26"	10 Pairs
01-0400-28	28"	75 lbc	28"	10 Paire

PRODUCT FEATURES:

- Standard with 1" over travel
- Available Lengths: 10" 28"
- Finish: Clear Zinc
- Side mounted with release latch for easy disconnect
- · Hold in detent
- 1/2" side spacing
- Load rating: 100 lbs./pair (22" length)
- Screw mounting system 32mm compatible
- 1/2" side clearance
- Comparable with Dynaslide® 4634, Accuride® 3834 and Knape & Vogt® 8405



ACCESSORIES

REAR MOUNT METAL SOCKET

• Material: Steel **OI-RMB-S**



REAR MOUNT PLASTIC SOCKET

• Material: ABS **OI-627**



SPACER

• Material: ABS **OI-3616**



EURO SLIDES



Superior Quality

		RECOMMENDED
PART#	SIZE	DRAWER WIDTH
OI-1500-10	10"	10"
OI-1500-12	12"	12"
OI-1500-14	14"	14"
OI-1500-16	16"	16"
OI-1500-18	18"	18"
OI-1500-20	20"	20"
OI-1500-22	22"	22"
OI-1500-24	24"	24"





PRODUCT FEATURES:

- Self-close / Stay-closed action
- · Load Capacity: 75 lbs.
- 32mm system screw hole pattern
- · Durable epoxy coated steel profiles
- Smooth & quiet nylon rollers
- Bottom mounting
- Drawer Extension (Travel): Length of slide minus 1-1/2"
- 1/2" side clearance



ACCESSORIES

REAR MOUNT PLASTIC SOCKET

• Material: ABS **OI-RMB**



REAR MOUNT PLASTIC SOCKET

• Material: ABS **OI-6402**



SPACER

• Material: ABS **OI-3602**



MILLER FASTBLOCK™

• Material: ABS



FC-MFB-WH 2 pc. pack





STAINLESS STEEL FULL EXTENSION DRAWER SLIDES



OI-3800S SERIES

75 lb. Capacity



PROFILE 12.2 (.48") 37.0 (1.46")

	SLIDE	TRAVEL	LOAD RATING
PART #	LENGTH	LENGTH	PER PAIR
OI-3800S-8	7.87"	7.54"	98 lbs.
OI-3800S-10	9.84"	9.57"	92 lbs.
OI-3800S-12	11.81"	12"	88 lbs.
OI-3800S-14	13.78"	14"	84 lbs.
OI-3800S-16	15.75"	16"	79 lbs.
OI-3800S-18	17.72"	18"	75 lbs.
OI-3800S-20	19.69"	20"	73 lbs.
OI-3800S-22	21.65"	22"	68 lbs.
OI-3800S-24	23.62"	24"	64 lbs.

PRODUCT FEATURES:

- 304 grade stainless steel
- 3 member full extension
- Ball bearing construction
- Front disconnect
- Positive stop
- Side mounting
- Non handed
- Screw sold separately

SCREW PART #	BULK CTN. QTY.		
SCR-8625PHZ	12,000		
#8 x 5/8" Pan Head Zinc			

OI-4500S SERIES

100 lb. Capacity



PROFILE 13.0 (.51") 45.0 (1.77")

PART#	SLIDE LENGTH	TRAVEL LENGTH	LOAD RATING PER PAIR
OI-4500S-10	9.84"	9.57"	115 lbs.
OI-4500S-12	11.81"	12"	111 lbs.
OI-4500S-14	13.78"	14"	108 lbs.
OI-4500S-16	15.75"	16"	104 lbs.
OI-4500S-18	17.72"	18"	100 lbs.
OI-4500S-20	19.69"	20"	97 lbs.
OI-4500S-22	21.65"	22"	95 lbs.
OI-4500S-24	23.62"	24"	92 lbs.
OI-4500S-26	25.59"	26"	90 lbs.
OI-4500S-28	27.56"	28"	87 lbs.

PRODUCT FEATURES:

- 304 grade stainless steel
- 3 member full extension
- Ball bearing construction
- Front disconnect
- Positive stop
- Side mounting
- Non handed
- Full travel
- Screw sold separately

SCREW PART#	BULK CTN. QTY
SCR-8625PHZ	12,000
#8 x 5/8" Pan	Head Zinc

ACCESSORIES

REAR MOUNT METAL SOCKET

• Material: Steel

OI-RMB-S



REAR MOUNT PLASTIC SOCKET

• Material: ABS

OI-627



SOCKET

• Material: ABS Ol-3616



100 LB. FULL EXTENSION BALL BEARING SLIDE



10 Pairs

10 Pairs

10 Pairs

10 Pairs

10 Pairs

OI-5000-20

OI-5000-22

OI-5000-24

OI-5000-26

OI-5000-28

20"

22"

24"

26"

28"

• Material: ABS

OI-648

95 lbs.

90 lbs.

85 lbs.

80 lbs.

75 lbs.

PENINSULA BRACKETS

12.3 mm (0.48 in.) is the actual size of the slide. Allow a min. of 12.7 mm (0.50 in.) for clearance.

(0:48)

PRODUCT FEATURES:

- · Lengths: 12" to 28"
- Finish: Clear Zinc
- Precision ball bearing slide for medium-duty applications in office and residential furniture
- · Drawer profile features an easy to operate disconnect finger release trigger
- · System 32 compatible hole
- · Drawer slide is non-handed
- New ECD™ easy close (soft close) device
- 1/2" side clearance

MOUNTING SCREWS SOLD SEPARATELY 16 pieces required per pair SCR-6625FHZ

See page 300 for our complete screw line

ACCESSORIES

REAR MOUNT PLASTIC SOCKETS

• Material: Steel **OI-5000B-S**



mm (in.)

SPACER

 Material: ABS **OI-3616**




200 LB. HEAVY DUTY FULL EXTENSION SLIDES





PART#	LENGTH	LOAD RATING	SIZE
OI-5210-14	14"	Dynamic to 200 lbs.	10 Pairs
OI-5210-16	16"	Dynamic to 200 lbs.	10 Pairs
OI-5210-18	18"	Dynamic to 200 lbs.	10 Pairs
OI-5210-20	20"	Dynamic to 200 lbs.	10 Pairs
OI-5210-22	22"	Dynamic to 200 lbs.	10 Pairs
OI-5210-24	24"	Dynamic to 200 lbs.	10 Pairs
OI-5210-26	26"	Dynamic to 200 lbs.	10 Pairs
OI-5210-28	28"	Dynamic to 200 lbs.	10 Pairs



12.9 mm (0.51 in.) is the actual size of the slide. Allow a min. of 13.1 mm (0.52 in.) for clearance.



See page 300 for our complete screw line

QUIK TRAY ROLL OUT SYSTEM







The "Simple Solution" for Maximizing Storage Space & Convenience

PRODUCT FEATURES:

- Material: ABS
- Can be used with face frame or frameless cabinets
- Installs easily with a screw driver & adjusts without tools

Hook Dowels are Included In All Kits




Unique hook dowels allows you to work with most full extension european & undermount drawer slides. Hooks get connect to drawer slides.

Standard Supports (All Inclusive Kits)

Includes 4 supports, 4 Hook Dowels (Full Extension/European) & Mounting Screws




1" Wide Quik Tray Support



PART #	THICKNESS	LENGTH	COLOR	SETS PER CARTON
QT10-*	1" W / .250" Standoff	20.125"	*WH - White / *CR - Cream	25



1-1/4" Wide Quik Tray Support




CETC DED

PART#	THICKNESS	LENGTH	COLOR	CARTON
QT14-*	1-1/4" W / .325" Standoff	20.125"	*WH - White / *CR - Cream	25



2" Wide Quik Tray Support



SETS DED

PART#	THICKNESS	LENGTH	COLOR	CARTON
QT20-*	2" Without Standoff	20.125"	*WH - White *CR - Cream	12

QUIK TRAY ROLL OUT SYSTEM







1-1/4" Wide Short Support Sets (All Inclusive Kit)

Includes 4 Supports, 4 Hook Dowels (Full Extension/European) & Mounting Screws

Only Works With QT-14-*





CETC DED


PART#	THICKNESS	LENGTH	COLOR	CARTON
QT14S-*	1-1/4" W / .325" Standoff	3-3/4"	*WH - White / *CR - Cream	25

Center Partition Support Set (All Inclusive Kit)

Includes 2 Partition Supports & Mounting Screws



Ideal For Double Door Application
Without A Face Frames



PART#	LENGTH	COLOR	CARTON
QTP-*	20.12"	*WH - White / *CR - Cream	12

Quik Tray Mounting Hardware



Hook dowel for undermount drawer slides

Set of 8 & Screws

3.00			
	.250	PART #	SETS PER CARTON
具		QTHK-U	50

77

11.5MM Tray Bumper Beige: 2 Bumpers & 2 Screws Per Set

See Page 309

18MM Tray Bumper Beige- 2

See Page 309

No Need To Change Existing Cabinets



Face Frame with Low Profile Hinge



Frameless Cabinet with Concealed Hinge



2" Support with Long Arm Hinge & Face Frame Cabinet



Short Supports for Low Profile Cabinets



Quik Tray supports can be mounted to center partition supports instead of wood stile

VERTICAL / PANTRY CABINET PULL-OUT HARDWARE



HEAVY DUTY PROGRESSIVE ACTION FULL EXTENSION CABINET SLIDES



(FROM 200-475 LBS. OF DYNAMIC LOAD BEARING CAPACITY)

TOP AND BOTTOM SLIDE WITH SOFT CLOSE MECHANISM

Ideally suited for tall kitchen pantries, vertical cabinet pull-outs at any height or width, heavy duty pull-out space saving applications, special projects or other architecturally engineered projects where smooth running and heavy use is critical

FEATURES	OI-775	OI-771
LOAD RATING	175 LBS	275 LBS
MAXIMUM CABINET HEIGHT	59"	-
BRAKE (OR STOP)	No	Yes

PRODUCT FEATURES:

- Material: White Powder Coated Cold Rolled Steel
- Floor mounted with top slide for lateral stability
- The delrin encased steel ball bearings provides a quiet and optimum movement
- Vertical and horizontal adjustment capabilities allows for alignment after install is complete
- ECD integrated easy (or soft) close device
- · No deflection when extended
- Double sided captive profile (775 ONLY)
- Extension is length of slide less approximately 3/4"
- No Lubrication Required!

Note: Lubrication must not be applied to any part of the slide as this will prevent the product from working properly


CLIDE LENGTH ACTUAL



OI-775









WEIGHT


	SLIDE LENGTH	ACTUAL		WEIGHT
PART#	(NOMINAL)	LENGTH	EXTENSION	BY LBS.
OI-775-16	16"	15.75"	15.16"	11 lbs.
OI-775-18	18"	17.72"	17.13"	12 lbs.
OI-775-20	20"	19.69"	19.10"	13.5 lbs.
OI-775-22	22"	21.65"	21.06"	14.5 lbs.
OI-775-24	24"	23.62"	23.03"	16 lbs.
OI-775-26	26"	25.59"	25.00"	17 lbs.
OI-775-28	28"	27.56"	26.97"	18 lbs.
OI-775-30	30"	29.53"	28.94"	20 lbs.



OI-771







 PART #
 SLIDE LENGTH (NOMINAL)
 ACTUAL LENGTH EXTENSION
 WEIGHT BY LBS.

 0I-771-22
 22"
 22.64"
 22.01"
 19.50 lbs.

VERTICAL / PANTRY CABINET PULL-OUT HARDWARE



HEAVY DUTY PROGRESSIVE ACTION FULL EXTENSION CABINET SLIDES



(FROM 200-475 LBS. OF DYNAMIC LOAD BEARING CAPACITY)

TOP AND BOTTOM SLIDE WITH SOFT CLOSE MECHANISM

Ideally suited for tall kitchen pantries, vertical cabinet pull-outs at any height or width, heavy duty pull-out space saving applications, special projects or other architecturally engineered projects where smooth running and heavy use is critical

FEATURES	OI-777
LOAD RATING	450 LBS
MAXIMUM CABINET HEIGHT	-
BRAKE (OR STOP)	Yes


PRODUCT FEATURES:


- Material: White Powder Coated Cold Rolled Steel
- Floor mounted with top slide for lateral stability
- The delrin encased steel ball bearings provides a quiet and optimum movement
- · Vertical and horizontal adjustment capabilities allows for alignment after install is complete
- ECD integrated easy (or soft) close device
- · No deflection when extended
- · Double sided captive profile (775 ONLY)
- Extension is length of slide less approximately 3/4"
- No Lubrication Required!


Note: Lubrication must not be applied to any part of the slide as this will prevent the product from working properly



TOP SLIDE







	SLIDE LENGTH	ACTUAL		WEIGHT
PART#	(NOMINAL)	LENGTH	EXTENSION	BY LBS.
OI-777-16	16"	15.74"	15.12"	20.50 lbs.
OI-777-18	18"	17.72"	17.09"	23 lbs.
OI-777-20	20"	19.69"	19.06"	25 lbs.
OI-777-22	22"	21.65"	21.02"	27.50 lbs.
OI-777-24	24"	23.62"	22.99"	30 lbs.
OI-777-26	26"	25.59"	24.96"	32 lbs.
OI-777-28	28"	27.55"	26.93"	34 lbs.
OI-777-30	30"	29.53"	28.9"	36.50 lbs.
OI-777-32	32"	31.50"	30.87"	39 lbs.
OI-777-34	34"	33.47"	32.83"	41.50 lbs
OI-777-36	36"	35.43"	34.80"	43.50 lbs
OI-777-EZ	Easy	Close Sys	tem Optional	

BOTTOM SLIDE




TEC 864 ONE PIECE HINGE 108° OPENING ANGLE - 1/4" TO 1-1/2" OVERLAY

FOR FACE FRAME APPLICATIONS


PRODUCT FEATURES:


- · Material: Steel with Zinc Finish
- 1 piece hinge & base plate combination
- Front locating tabs position hinge on face frame

Overall Dimensions



45mm Drill Pattern





Side Mount Plate



For Smaller or Larger Than Standard 3/4" Face Frames

Wrap Around Plate



For Standard 3/4" Face Frames 3-Dimensional Adjustment

- 1. Side Adjustment: +/- 1/16" (1.5mm)
- 2. Height Adjustment: +/- 3/32" (2mm)
- 3. Depth Adjustment: + 3/32" (2mm), 1/16" (1mm)

SIDE MOUNT

PART#	OVERLAY	PLATE TYPE	CARTON QTY.
VS8-108-25S	1/4"		300
VS8-108-50S	1/2"		300
VS8-108-75S	3/4"		300
VS8-108-100S	1"	DOWELLED	300
VS8-108-125S	1-1/4"		300
VS8-108-138S	1-3/8"		300
VS8-108-150S	1-1/2"		300
VS-108-25S	1/4"		300
VS-108-50S	1/2"		300
VS-108-75S	3/4"		300
VS-108-100S	1"	SCREW-ON	300
VS-108-125S	1-1/4"		300
VS-108-138S	1-3/8"		300
VS-108-150S	1-1/2"		300

WRAP AROUND


PART#	OVERLAY	PLATE TYPE	CARTON QTY.
VS8-108-25W	1/4"		300
VS8-108-50W	1/2"		300
VS8-108-75W	3/4"		300
VS8-108-100W	1"	DOWELLED	300
VS8-108-125W	1-1/4"		300
VS8-108-138W	1-3/8"		300
VS8-108-150W	1-1/2"		300
VS-108-25W	1/4"		300
VS-108-50W	1/2"		300
VS-108-75W	3/4"	SCREW-ON	300
VS-108-125W	1-1/4"		300
VS-108-138W	1-3/8"		300
VS-108-150W	1-1/2"		300

UNI-SOFT CLOSE ADAPTOR



PRODUCT FEATURES:

- Material: Plastic with brushed nickel finish to blend well with hinge finish
- Works for face frame cabinets on all overlays and frameless cabinets on full overlay doors.
- Manually adjustable to desired closing speed.
- Mounts easy in corners with #6 x 3/4" wood screws included.
- 11/16" (17mm) Clearance required.
- Ideal when upgrading existing cabinets or working with other hinges options.



PART#	DESCRIPTION
UNI-SFT	Individual Polybag
UNI-SET-25	25 piece bag






TEC ONE PIECE SOFT CLOSE HINGE 108° OPENING ANGLE - 1/4" TO 1" OVERLAY FOR FACE FRAME APPLICATIONS




PRODUCT FEATURES:


- Material: Steel with Zinc Finish
- Soft close damper premounted in hinge cup
- 1 piece hinge & base plate combination
- Front locating tabs position hinge on face frame

Overall Dimensions



45mm Drill Pattern





SIDE MOUNT

PART#	OVERLAY	PLATE TYPE
VS8-45U-25S	1/4"	DOWELLED

Technical Information

There are numerous variables that will determine the choice of hinge. Determine the requirements of the application. Consider the following points based on the door to cabinet application.

- 1. Door overlay
- 2. Adjustment requirements:
 - a. Height only
 - b. Height and side
 - c. Height, side and depth
- 3. Base plate mounting to face frame:
 - a. Wrap-around 3/4" thick frames only
 - b. Side mount frames thicker than 3/4"
 - c. Face mount any overlay greater than 1-3/8"
 - d. MDF material mounting into end grain
- Door removal:
 - a. With base plate mounting screw (one-piece hinges)
 - b. With depth adjustment screw (two-piece hinges)
- 5. Door clearance/hinge arm clearance (for interior rollout trays)
- 6. Door gap-distance between face frame and the back of the closed door
- 7. Minimum reveal distance between two doors hinged back-to-back
- B. Door thickness thicker doors can restrict opening angle and minimum reveal
- 9. Hinge cup boring pattern for dowelled hinges
- 10. Door opening angle

Side Mount Plate



For Smaller or Larger Than Standard 3/4" Face Frames

Wrap Around Plate



For Standard 3/4" Face Frames 3-Dimensional Adjustment


- 1. Side Adjustment: +/- 1/16" (1.5mm)
- 2. Height Adjustment: +/- 3/32" (2mm)
- 3. Depth Adjustment: + 3/32" (2mm), 1/32" (.5mm)

WRAP AROUND

PART#	OVERLAY	PLATE TYPE
VS8-45U-25W	1/4"	
VS8-45U-50W	1/2"	DOWELLED
VS8-45U-75W	3/4"	DOWELLED
VS8-45U-100W	1"	
VS-45U-25W	1/4"	
VS-45U-50W	1/2"	SCREW-ON
VS-45U-75W	3/4"	SCREW-ON
VS-45U-100W	1"	

Number of hinges per door

The number of hinges required on the size and weight of the door. The distance between the hinges should be spaced as wide as possible. Use the diagram to determine the number of hinges needed. These recommendations are for doors without any accessory attachments.






NEXIS CLICK-ON QUICK MOUNTING HINGES

PRODUCT FEATURES:

Door Size Guidelines


- All Metal, Nickel Plated, self closing hinges.
- Full overlay, half overlay, and in-set options.
- Screw-on or doweled (knock-in) options available.
- All hinges work with soft close system
 - see individual charts below.
- Plate options available for Face Frame or Frameless applications.



100° OPENING

SPECIFICATIONS:





• Works with up to 7/8" (22mm) thick door.

SCREW-ON







		PCS. PER	
PART#	DESCRIPTION	CARTON	
CS4-100S-F	Full Overlay (00)	250	
CS4-100S-H	Half Overlay (08)	250	
CS4-100S-I	Inset (15)	250	

PLATES FOR FACE FRAME APPLICATIONS	PLATES FOR FRAMELESS APPLICATIONS	SOFT CLOSE
A, B, C	D, E	See Option A, pg. 329

DOWELED (Knock-In)



		I CO. I LIX	
PART#	DESCRIPTION	CARTON	
CS4-100D-F	Full Overlay (00)	250	
CS4-100D-H	Half Overlay (08)	250	
CS4-100D-I	Inset (15)	250	

PLATES FOR FACE FRAME APPLICATIONS	PLATES FOR FRAMELESS APPLICATIONS	SOFT CLOSE
A, B, C	D, E	See Option A, pg. 329

6 x 5/8" Zinc Plated Screw 500 pcs. per carton

^{*} INSTALLATION DIMENSIONS AVAILABLE UPON REQUEST. ALL MEASUREMENTS ARE IN MILLIMETERS. CS-SCREW


NEXIS CLICK-ON QUICK MOUNTING HINGES



PRODUCT FEATURES:

· Material: Metal Nickel Plated





SCREW-ON







PART#	DESCRIPTION	THICKNESS	CARTON
CS22-110S-F	110° Full Overlay (00)		250
CS22-110S-H	110° Half Overlay (08)	25/32"	250
CS04-110S-I	110º Inset (15)		250
CS29-125S-F	125° Full Overlay (00)	3/4"	250
CS29-125S-H	125° Half Overlay (08)	3/4	250
CS65-170S-F	170° Full Overlay (00)	1"	250
CS65-170S-H	170° Half Overlay (08)	'	250

DOWELED (Knock-In)







PART#	DESCRIPTION	THICKNESS	CARTON
CS22-110D-F	110° Full Overlay (00)		250
CS22-110D-H	110° Half Overlay (08)	25/32"	250
CS04-110D-I	110º Inset (15)		250
CS29-125D-F	125° Full Overlay (00)	3/4"	250
CS29-125D-H	125° Half Overlay (08)	3/4	250
CS65-170D-F	170° Full Overlay (00)	1"	250
CS65-170D-H	170º Half Overlay (08)	1	250

PLATES FOR FACE FRAME APPLICATIONS	PLATES FOR FRAMELESS APPLICATIONS	SOFT CLOSE
A, B, C	D, E	See Option A, pg. 329 (For 100°, 110° & 125° Only)

NEXIS IMPRESSO WITH "TOOL-LESS" QUICK MOUNTING TECHNOLOGY

PRODUCT FEATURES:

- · Impresso hinges are perfect for door materials such as Particle Board, Solid Wood and MDF.
- Impresso securely fits and does not allow twisting of the hinge due to a 3-point connection of the hinge cup.
- Material: Metal Nickel Plated

BORING PATTERN OVERALL CUP DOWELED 60 Fits 42mm - 45mm hole patterns SIDE VIEW Minimum cup depth •110° - 11.5mm or .46" • 125° - 12mm or .48" • 170° - 11mm or .44"

EASY TO INSTALL!

- 1. Insert Impresso hinges into the door boring.
- 2. Close the flap of the hinge cup, and you are done!













DOWELED (Knock-In)





		DOOR	PCS. PER
PART#	DESCRIPTION	THICKNESS	CARTON
CST22-110-F	110° Full Overlay (00)	25/32"	125
CST22-110-H	110° Half Overlay (08)	23/32	125
CST29-125-F	125° Full Overlay (00)	3/4"	125
CST29-125-H	125° Half Overlay (08)	3/4	125
CST65-170-F	170° Full Overlay (00)	1"	50
CST65-170-H	170° Half Overlay (08)	1	50

PLATES FOR FACE FRAME APPLICATIONS	PLATES FOR FRAMELESS APPLICATIONS	SOFT CLOSE
A, B, C	D, E	See Option B, pg. 329

* INSTALLATION DIMENSIONS AVAILABLE UPON REQUEST. ALL MEASUREMENTS ARE IN MILLIMETERS. (Screw-on only) CS-SCREW..... 6 x 5/8" Zinc Plated Screw 500 pcs. per carton - No Broken Cartons

NEXIS MOUNTING PLATES



PLEASE REFER TO CHART BELOW WHEN PURCHASING PLATES FOR HINGES DIFFERENT COMBINATIONS WILL YIELD DIFFERENT RESULTS

	HINGES	FULL - 00	HALF - 08	INSET - 15
	"00"	Full - 3/4"	Half - 3/4"	Inset
FRAMELESS	"02"	Full - 5/8"	Half - 5/8"	Inset
PLATES	"08"	Half	Inset	N/A
	"18"	Inset	N/A	N/A
EAGE EDAME	"00"	5/8" - 3/4"	3/8"	N/A
FACE FRAME PLATES	"04"	1/2"	1/4"	N/A
PLAILS	"02"	N/A	Inset	N/A

Boring distance will affect overlay result; always prepare a mock up before boring doors.

FOR FACE FRAME APPLICATIONS


· Nickel Plated.

- · All adjustments can be made independently.
- 6 way adjustment: up and down, in and out, and side to side. Mounts with wood screws (not included).

• Height and depth adjustable.

A. SPECIAL PLATE FOR FACE FRAME






PART#	HINGE TYPE	DOOR OVERLAY		PCS. PER CARTON
CSP-FF88-00	Click-on Twin	1/8" to 3/4"	"00"	250
CSP-FF88-04	Click-on Twin	1/8" to 3/4"	"04"	250

3D CAMPLATE






DADT#	HINGE	DOOR		PCS. PER
PART#	TYPE	OVERLAY	ITPE	CARTON
CSP-FF91-00	Click-on Twin	1/8" to 3/4"	"00"	250
CSP-FF91-04	Click-on Twin	1/8" to 3/4"	"04"	250

C. BEADED INSET





PART#	HINGE TYPE	DOOR OVERLAY		PCS. PER CARTON
CSP-FF90-02	Click-on Twin	Inset	"02"	250

FOR FRAMELESS APPLICATIONS


- Nickel Plated.
- · Adjustments can be made independently: up and down.
- · Height and depth adjustable.
- · Mounts with wood screws (not included).

D. SUPER CLICK



	HINGE	DOOR	PLATE	PCS. PER
PART#	TYPE	OVERLAY	TYPE	CARTON
CSP-FR55-00	Click-on Twin	Full, Half, Inset	"00"	250
CSP-FR55-08	Click-on Twin	Half, Inset	"08"	250
CSP-FR55-18	Click-on Twin	Inset Only	"18"	250

E. 3D ADJUSTABLE EURO CAM



PART#	HINGE TYPE	DOOR OVERLAY		PCS. PER CARTON
CSP-FR70-00	Click-on Twin	Full, Half, Inset	"00"	250
CSP-FR70-08	Click-on Twin	Half, Inset	"08"	250

* INSTALLATION DIMENSIONS AVAILABLE UPON REQUEST. ALL MEASUREMENTS ARE IN MILLIMETERS.

CS-SCREW

6 x 5/8" Zinc Plated Screw 500 pcs. per carton

NEXIS SOFT CLOSE SYSTEM

This unique design defines a new closing of doors. The motion of the doors is softly slowed down and the door self closes softly and quietly • Toolless. • Quick and easy to install. • Minimum one set required per two hinges.



OPTION A: SOFT CLOSE FOR NEXIS HINGES (PART #- CS-*)











PART# CS-SOFT

NOTE: WORKS WITH 100°, 110° & 125° ONLY

EACH SET INCLUDES:

- 1 Soft Close CS adapter with pre-mounted Soft Close.
 - 1 hinge cup cover cap.
 - 2 hinge arm cover caps.

CS-SCREW

6 x 5/8" zinc plated screw for "CS" hinges.



HALF OVERLAY









PART# CST-SOFT

OPTION B: SOFT CLOSE FOR IMPRESSO HINGES (PART #- CST-*)

EACH SET INCLUDES:

- 1 Soft Close CST adapter.
- 1 Soft Close CST damper.
- 2 hinge arm cover caps.

SPECIALITY HINGES


F 95° OPENING FOR THICK DOORS





PART#	DESCRIPTION	CARTON
CS5-95D-F	Full Overlay (00) Thick Door	250
CS5-95D-H	Half Overlay (08) Thick Door	250
CS5-95D-I	Inset (15) Thick Door	250

DOWELED (Knock-In)



PLATES FOR FACE FRAME APPLICATIONS	PLATES FOR FRAMELESS APPLICATIONS	SOFT CLOSE
A, B, C	D, E	See Option A, above.

CORNER HINGES



			PCS. PER
PA	RT#	DESCRIPTION	CARTON
CS5	/45-I	45° Corner	125
CS5	/90-I	90° Corner	125
CS/D	-PCC	Pie Cut Corner	125

PLATES FOR FACE FRAME APPLICATIONS	PLATES FOR FRAMELESS APPLICATIONS	SOFT CLOSE
A, B, C	D, E	See Option A, above.

DOWELED (Knock-In)

SPECIFICATIONS: CS/45-I & CS/90-I



SPECIFICATIONS: CS/D-PCC OVERALL CUP 49 **BORING PATTERN**



* INSTALLATION DIMENSIONS AVAILABLE UPON REQUEST. ALL MEASUREMENTS ARE IN MILLIMETERS.

CS-SCREW

6 x 5/8" Zinc Plated Screw 500 pcs. per carton

GRASS INSTITUTIONAL HINGES

PRODUCT FEATURES:

- All metal diecast construction for extreme durability in black & nickel finishes.
- Toolless snap-on mounting for quick & easy installation.
- Side-to-Side adjustment of -2mm(1/16") & height adjustment of +/-2mm(1/16").
- Hinge cup has 35mm diameter with a 45/9.5mm boring pattern (similar to Blum).
- · Designed for Frameless Cabinet Construction.
- Opening angles range from 180° 270° depending on your application.
- Meets ANSI/BHMA A 156.9 2003 Grade 1 Requirements when the screw & adjustment tabs are in place.
- Cover caps (included) conceal mounting screws.

PART#

· One hinge cup works arms.

	The state of

	TYPE	BLACK	NICKEL
HINGE CUP	SCREW-ON	MBS-8010-BK	MBS-8010-N
HINGE COP	DOWELLED	MBD-8010-BK	MBD-8010-N
FULL OVERLAY	270°	MB-8310-BK	MB-8310-N
HINGE ARM	270	INID-02 I U-DK	INID-02 I D-IN
HALF OVERLAY	230°	MB-8510-BK	MB-8510-N
HINGE ARM	230	MD-02 I 0-DK	MID-0210-M
COMMON PANEL		MB-8610-BK	MB-8610-N
(INSET) HINGE ARM	100	INID-00 I U-DIV	INID-00 I D-IN
EURO-SCREWS FOR	 N/A	MB-SCREW [^]	
HINGE ARM #6 x 13.		#6 x 13.5mm	Euro Screw

^ 2 SCREWS REQUIRED FOR HINGE ARM MOUNTING

1/2" OVERLAY INSTITUTIONAL HINGE

Material: Steel


• 2-3/4" Five

Knuckle Hinge.

• Designed for 32mm hole system.

 Radius ground hospital tips.

Matte Chrome finish.



44 lb.

Load

Rating

DIMENSIONS

PART# A B C
INSHIN-34 3/4" 3/4" 23/32"

32mm OVERLAY INSTITUTIONAL HINGE

Gloss White, Gloss Black, Dull Chrome

Material: Steel

Made in USA.

- 2 3/4" Five Knuckle Hinge.
- Radius Ground Hospital Tips For Increased Safety.
- Designed for 32mm Hole System.
- Radius Corners For Easy Mortising
- ANSI/BHMA A156.9 Grade 1.



PART# A B C
IH-E60- 3/4" 3/4" 23/32"
IH-G60- 3/4" 13/16" 23/32"

FLAP DOOR HINGE



Material: Steel



- Opening angle 90°.
- For flap door thickness up to 20mm.
- Cup boring cover.
- Bottom and Flap door are flush inside the cabinet when doors are open.
- 3-D Adjustable.

PART# PCS. PER CARTON
FLAP-735 100

DOUBLE ACTION SPRING HINGE

Material: Steel

- · Allows door to swing back and forth.
- For doors up to 1-1/8" thick.
- Screws & instructions included.
- Dimensions: 4-7/8" high x 3-1/2" wide.




PART# COLOR
DAH-BRS Brass
DAH-BLK Black

NO-BORE GLASS DOOR HINGE

Material: Steel

• For 1/4" Glass.





PART # COLOR 30023-CHR Chrome

CABINET HINGES & DAMPER

OPI SERIES - SOFT CLOSE PNEUMATIC HINGE



PRODUCT FEATURES:

• NO MORE SLAMMED DOORS!

Pneumatic cylinder provides soft closing action.

• NO EXTRA ACCESSORIES!

Built-in cylinder makes closing doors easy.

- · Clip on system.
- Screws included.









CONCEALED METAL HINGE

ONE HINGES DOES IT ALL; FITS ANY FRAME-LESS CABINET.

The CONCEALED METAL HINGE is surface mounted - this means no routing of door or cabinet. Made of cold rolled steel with a bright nickel finish and a stainless steel spring. All pins & rivets are zinc plated for long life.

- · Overlay, adjustable from 0 to 3/4".
- 3/8" inset.
- Full inset.
- Allows door to open over 150°.
- Built-in closing mechanism.
- · Screws not included.

PART# SG-225

SOLID BRASS NON-MORTISE CYLINDER HINGE

SOLID BRASS NON-MORTISE CYLINDER HINGE



FOR DOORS OR FLAPS 180 DEGREE

		FOR WOOD
PART #	SIZE	THICKNESS
H-240-10	10mm	1/2"
H-240-12	12mm	5/8"
H-240-14	14mm	3/4"
H-240-16	16mm	7/8"
H_240_19	10mm	1 1/0"

Α	В	D	E
10	11mm (7/16") Approx.	16.5mm (21/32") Approx.	2.5mm (3/32") Approx.
12	13.5mm (17/32") Approx.	20mm (25/32") Approx.	3.5mm (9/64") Approx.
14	15.5mm (5/8") Approx.	23mm (29/32") Approx.	3mm (1/8") Approx.
16	16.5mm (21/32") Approx.	25mm (1") Approx.	3mm (1/8") Approx.
18	17.5mm (11/16") Approx.	27mm (1-1/16") Approx.	3mm (1/8") Approx.

SOFT CLOSE DAMPERS

PRODUCT FEATURES:


- Softens the impact of the door against the cabinet.
- Can be recessed into the cabinet side or mounted to the table.
- Suitable for double doors, inset doors & face frame applications.
- · Use 2 dampers for door heights over 3'.

PART# SFT-MAD-GY

MEDIUM DUTY








SIDE MOUNTED





TOTALLY CLEAR FLAT HINGES

CLEAR P.E.T.G./PVC with glue groove 5 Ft. Lengths




CLEAR ACRYLIC/PVC 5 Ft. Lengths



EXTRUDED HINGE

CLEAR URETHANE & ACRYLIC
4 Ft. Lengths U.V. Stabilized for Outdoor Use!




PART # F2000-CL

PLASTIC PIANO HINGE

Clear or Black 12" Long x 1-3/4" Wide

- Replaces metal hinges that require on to drill, tap or rivet.
- Outer bonding surface is wide for added bonding strength.
- Easily cuts to small size without falling apart.

PART#	MATERIAL
PH-175-12CL	Acrylic
PH-175-12BK	ABS




ACRYLIC HASP

Clear, Black or White 2-3/8" Long x 1-1/16" Wide x 1/8" Thick


Bottom section of hasp is reversible for either corner or flat mounting.

Pre-determine assembly before inserting pin completely!



PART #	COLOR
HSP-110-CL	Clear
HSP-110-BK	Black
HSP-110-WH	White


CLEAR ACRYLIC HINGE



PART # 150-1375 175-150

PLASTIC HINGES CLEAR ECONOMY

ACRYLIC HINGE




Larger Quantities Available - Please Inquire

PART # EC175-150

POLYPROPYLENE HINGE


Black or White Screw Size Recommended #10 Countersunk (not included)



Won't Rust - Quiet - Long Life

PART # COLOR 200-200-WH White 200-200-BK Black

MONSTER HINGE™



Material: Acrylic DR101 (Clear), ABS (Black)


- New design makes this hinge virtually unbreakable!
- Large ribbed sections added for superior strength!
- Larger pin diameter (.190" dia.)

PART#


DESCRIPTION


MONSTER-HINGE-CL MONSTER-HINGE-BK Clear Acrylic 1-5/16" L x 2" W x 1/2" Thick Hinge Black ABS 1-5/16" L x 2" W x 1/2" Thick Hinge

PLASTIC PANEL HINGE



PLASTIC TEE HINGE







CONTINUOUS STEEL PIANO HINGE

AVAILABLE FINISHES:


Nickel, Brite Brass, *304 Grade Stainless Steel, Statuary Bronze, Electro Black Lacquered 4 SIZES:

1-1/4"x 72", 1-1/2" x 72", 2" x 72" & 1-1/4" x 100'












NOTE: All measurements are approximate; please refrain from drilling your holes until product is received.



	Α	В	С	D	
1	1-1/4"	2"	1/2"	.750"	
2	1-1/2"	2"	1/2"	.876"	
3	2"	2"	1/2"	1.13"	
4	1-1/4"	2"	1/2"	.75"	
	2	1 1-1/4" 2 1-1/2" 3 2"	1 1-1/4" 2" 2 1-1/2" 2" 3 2" 2"	1 1-1/4" 2" 1/2" 2 1-1/2" 2" 1/2" 3 2" 2" 1/2"	

DIMENSIONS

If you are interested in aluminum hinges or custom lengths, please inquire.

PIANO HINGE FLAT PHILLIPS SCREWS

PART #	FINISH	WORKS WITH	HEAD SIZE
SCR-5625FHZ	Zinc	all piano hinges	#5 x 5/8"
SCR-5625FHB	Black	except PH-*-72SS	#5 x 5/8"
SCR-6625FHZ	Zinc	only PH-*-72SS	#6 x 5/8"
		(stainless steel hole is larger)	

For Our Complete Line Of Screws See Page 300

72 screws are required per piece.

SOFT CLOSING DAMPENING HINGE




HG-JHM16/20





PRODUCT FEATURES:


- No more lids that slam shut! This hinge has a built-in soft close dampening mechanism.
- · Mortise mounting.
- Sold in pairs, handed.
- Choice of Black or White cover.
- Ideal for small to large lids.
- Calculate torque required to determine which hinge will work best for your application.
- Torque Calculation: Torque = Door Height x 1/2 x Door Weight.
- For upward opening applications only.











HG-JHM16

.118"



Bracket / Mounting Plate

No.	PART NAME	MATERIAL	FINISH / COLOR
1	Bracket	Polyacetal	Black
2	Mounting Plate	Aluminum	Black
3	Face Plate	ABS	Black / White
4	Damper	304 Stainless Steel	Plain





Black Cover

White Cover

PART#	COLOR	DESCRIPTION	*TORQUE PER PAIR	
HG-JHM16-34	Black	Pody	17.4 - 29.5 lbs•in	
HG-JHM16-50	DIACK	Body	29.5 - 43.4 lbs•in	
HG-JHM16-BL	Black	Face Plate		
HG-JHM16-WT	White	race Plate	-	
HG-JHM20-80	Black	Body	53 - 70.8 lbs•in	
HG-JHM20-BL	Black	Cover		
HG-JHM20-WH	White	Cover	-	
* Torque measurement is referring to pounds of force per inch (lbs•in)				

ADJUSTABLE SOFT DOWN STAY




KEEPS FLAP/LIDS FROM SLAMMING SHUT & FLYING OPEN





Torque Calculation: Torque = Door Height x 1/2 x Door Weight
Per Piece: 20 - 70 kg • cm (19 - 60 lbs • inch)
Per Pair: 40 - 140 kg • cm (38 - 120 lbs • inch)




PRODUCT FEATURES:

- Material: Zinc Alloy & Steel
- Finish: Nickel
- For piano / butt / concealed hinges
- Screws included
- Speed adjustment screw for soft close

NSDX-10

90° Opening · For downward opening flap door · Designed to hold door in closed position






PART #	MOUNTING SIDE	OPENING ANGLE
NSDX-10RK	Right	90°
NSDX-10LK	Left	90°

NSDX-20

70° or 105° Opening · For top opening flap door · Designed to hold door in fully opened position






	MOUNTING	OPENING
PART #	SIDE	ANGLE
NSDX-20RK	Right	70° or 105°
NSDX-20LK	Left	70° or 105°

NSDX-35

80°, 90° or 100° Opening · For upward opening flap door · Designed to hold door in fully opened position





	MOUNTING	OPENING
PART #	SIDE	ANGLE
NSDX-35RK	Right	80°, 90° & 100°
NSDX-35LK	Left	80°, 90° & 100°

Face Frame Bracket



For face frame applications use one bracket per arm

PART # FFCB-SD-1

* All lid stays include the standard mounting plate for wood doors (NSDX-SZ). Mouting plates for aluminum frame (NSDX-AZ) and glass doors (NSDX-GZ) also available. Please Inquire

SOFT DOWN STAY






Face Frame Bracket



For face frame applications use one bracket per arm

PART #
FFCB-SD-1

SDS-100-TV/TVZ (Short Arm)



PRODUCT FEATURES:

- Material: Steel and Zinc Alloy with Black or White Plastic Housing
- For DOWNWARD-OPENING FLAP DOOR with piano, butt or drop hinges (SOLD SEPARATELY)
- Designed for small height door application
- SDS-C100TV has a catch to hold the lid closed in position
- SDS-100TV does not have a catch feature and is designed to be used with a magnetic catch or touch latch

PART #	COLOR	TYPE	* TORQUE PER PIECE	* TORQUE PER PAIR
SDS-100W-TV	White	Without	5-12kgf•cm	10-24kgf•cm
SDS-100B-TV	Black	Catch	(4.3-10.4 lbs•in)	(8.7-20.1 lbs•in)
SDS-C100W-TV	White	With	5-12kgf•cm	10-24kgf•cm
SDS-C100B-TV	Black	Catch	(4.3-10.4 lbs•in)	(8.7-20.1 lbs•in)
SDS-100W-TVZ	White	Without	16.5-37.6kgf•cm	33-75.2kgf•cm
SDS-100B-TVZ	Black	Catch	(14.3-32.6 lbs•in)	(28.6-65.2 lbs•in)
SDS-C100W-TVZ	White	With	16.5-37.6kgf•cm	33-75.2kgf•cm
SDS-C100B-TVZ	Black	Catch	(14.3-32.6 lbs•in)	(28.6-65.2 lbs•in)

* Torque measurement is referring to kilograms of force per centimeter (kgf*cm) or pounds of force per inch (lbs*in).

Torque Calculation: Torque = Door Height x 1/2 x Door Weight


LID STAY

Stroke for stop release

PART # LS-195

PRODUCT FEATURES:

- Material: 304 Stainless Steel with Satin Finish
- · Positive stop to keep flap open
- Left or right hand installation
- 33 lbs. load each
- · Screws not included
- · Must install parallel to sidewall




SOFT CLOSING LID STAY



SLS-ELAN





3 functions on 1 stay










PRODUCT FEATURES:

- · LAPCON stay for upward-opening flap doors
- Lift-assist mechanism for extra light-opening
- Damper equipped for soft & silent closing at the end
- Slim design and installed location maximizes space inside of cabinet
- Simply installation by aligning body to edge of cabinet
- Single or pair use allows wide range of door size/weight
- Recognized by LGA for 40,000 cycles



DOOR WEIGHT RANGE TABLE (LBS.)

DOOK WEIGHT KANGE IMBEE (EBG.)								
DOOR	SINGLE USE			PAIR USE				
HEIGHT	M-T	YPE	H-T	YPE	M-TYPE		H-TYPE	
(inches)	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
12"	8.0	10.8	10.8	14.5	16.0	21.7	21.7	29.0
13"	7.4	10.0	10.0	13.4	14.8	20.0	20.0	26.8
14"	6.9	9.3	9.3	12.4	13.7	18.6	18.6	24.9
15"	6.4	8.7	8.7	11.6	12.8	17.3	17.3	23.2
16"	6.0	8.1	8.1	10.9	12.0	16.3	16.3	21.8
17"	5.6	7.6	7.6	10.2	11.3	15.3	15.3	20.5
18"	5.3	7.2	7.2	9.7	10.7	14.4	14.4	19.3
19"	5.1	6.8	6.8	9.2	10.1	13.7	13.7	18.3
20"	4.8	6.5	6.5	8.7	9.6	13.0	13.0	17.4
21"	4.6	6.2	6.2	8.3	9.1	12.4	12.4	16.6
22"	4.4	5.9	5.9	7.9	8.7	11.8	11.8	15.8
23"	4.2	5.7	5.7	7.6	8.3	11.3	11.3	15.1
24"	4.0	5.4	5.4	7.3	8.0	10.8	10.8	14.5
25"	3.8	5.2	5.2	7.0	7.7	10.4	10.4	13.9
26"	3.7	5.0	5.0	6.7	7.4	10.0	10.0	13.4
27"	3.6	4.8	4.8	6.4	7.1	9.6	9.6	12.9
28"	3.4	4.6	4.6	6.2	6.9	9.3	9.3	12.4

Single or Pair use depending on door size

		TORQUE		FINISH/
PART#	TYPE	PER PIECE	MATERIAL	COLOR
SLS-ELAN-MR (Right)	M-Type	55-75 kg-cm	. Alumainum	• Anadizad
SLS-ELAN-ML (Left)	(Medium Duty)	(48-65 lbs•in)	Aluminum Steel	AnodizedGalvanized
SLS-ELAN-HR (Right)	H-Type	75-100 kg-cm	• ABS	Light Gray
SLS-ELAN-HL (Left)	(Heavy Duty)	(65-87 lbs•in)	- 700	Light Gray



Face Frame Bracket

For face frame applications use one bracket per arm

PART #
FFCB-SLS


SOFT CLOSING LID STAY




SLU-ELAN









PRODUCT FEATURES:

- Material: Steel, Zinc Alloy, Aluminum & Light Gray ABS
- Lift assist mechanism for extra light opening
- Free stop so door stays open in any desired position
- Damper equipped for soft and silent closing
- No hinges required
- Only a 6" gap from the face of the cabinet to the back of the door when fully open
- Trimmable connecting bar (sold separately) to fit any width cabinets
- Recommended door sizes and weight: Max Width: 59", Height: 15-3/8" 19-11/16" & Weight: 11~24.2 lbs./door



	DOOR	
PART #	WEIGHT	
SLU-ELAN-S4	11 - 14.3 lbs.	
SLU-ELAN-L4	14.3 - 17.6 lbs.	
SLU-ELAN-M4	17.6 - 20.9 lbs.	
SLU-ELAN-H4	20.9 - 24.2 lbs.	

Connecting Bar (Sold Separately)

	CABINET
PART #	WIDTH
ELB-480	23-5/8"
ELB-780	35-1/2"
ELB-1080	47-1/4"
ELB-1380	59"

Face Frame Bracket



For face frame applications use one bracket per arm

PART # FFCB-SLU

LATERAL OPENING DOOR HINGE

SUGATSUNE

LATERAL SWING MECHANISM










PRODUCT FEATURES:

- Material: Anodized Nickel Finish & Steel/Aluminum
- Ideal for tight front space application
- Allows doors to swing out laterally in a small radius
- Doors will not get in the way when fully opened thus providing full access to the cabinet
- · Door has free swing & soft close
- Standard 32mm system mounting
- Can be used in single or double door configuration
- · Use with frameless cabinets, optional face frame cabinet bracket available

Easy Access with Full Opening



Lateral Swing Mechanism



Ideal for tight front space application

PARTS INCLUDED:




- Hinge Body: 2 pcs.Mounting Plates: 2 pcs. · Connecting Bar: 1 pcs. Cover Cap: 2 pcs.

EACH BASIC KIT DOES 1 DOOR






Snap-on Installation



4Way Adjustment




FACE FRAME CABINET OPTIONS








Can be Opened from Various Points



Please note handle position before installation. Handle may interfere with hinge.

Various Applications



Right / Left Combination Corner Use

Island Kitchen

Optional bracket to use LIN-X450 & LIN-X600 with face frame cabinets.

PART #	DOOR WIDTH	DOOR HEIGHT	DOOR THICKNESS	DOOR WEIGHT
LIN-X450	400-500mm	600-900mm	15-24mm	max 7kg
	15-3/4" - 19-11/16"	23-5/8" - 35-7/16"	19/32" - 61/64"	15.4 lbs./door
LIN-X600	550-650mm	600-900mm	15-24mm	max 9kg
	21-21/32" - 25-19/32"	23-5/8" - 35-7/16"	19/32" - 61/64"	19.8 lbs./door

NOTE: When working with taller/heavier doors, please inquire!!! Many options available!

SWING LIFT MECHANISM








PRODUCT FEATURES:

- Material: Nickel Plated Steel with Gray Plastic Housing
- Screws included
- Adjustable arm mounting plate for various door sizes
- Successfully passed 30,000 open / close private cycle tests
- Patented lapcon technology provides smooth and quiet motion

LIFT UP MECHANISM






PART#	DOOR WEIGHT	DOOR HEIGHT	DOOR WIDTH
SLUN-3N	6.2 - 8.4 lbs.		
SLUN-4N	8.4 - 10.6 lbs.	15-23/64" - 17-23/32"	23-5/8" - 35-7/16"
SLUN-5N	10.6 - 12.8 lbs.		

SWING DOWN MECHANISM






PART#	DOOR WEIGHT	DOOR HEIGHT	DOOR WIDTH
SLD-3	6.6 - 8.8 lbs.		
SLD-4	8.8 - 11.0 lbs.	14-1/8" - 15-3/4"	23-5/8" - 35-7/16"
SLD-5	11.0 - 13.2 lbs.		

BI-FOLD LIFT UP MECHANISM






PART#	DOOR WEIGHT	DOOR HEIGHT	DOOR WIDTH
HBFN-2M	5.5 - 7.7 lbs.		
HBFN-3M	7.9 - 9.9 lbs.	12-19/32" - 14-9/16"	17-23/32" - 35-7/16"
HRFN-4M	9 9 - 12 1 lbs		

OPI ECONOMY SERIES: "LIFT - UP" GAS SPRING

PRODUCT FEATURES:

- Suitable for face frame and frameless applications.
- Suitable for wood and aluminum doors.
- No lubrication required, (NOTE: If lubricated, product will not operate properly).
- Set includes: 2 gas springs, 2 sets of mounting brackets and screws.
- Finish: Silver, all metal construction.

PART # FORCE
LFTUP-100SV 100n (22.5 lbs)
LFTUP-150SV 150n (33.7 lbs)




4.8

10.8"

Gas Springs Selection Guide

Door Weight	2 -3 kg	3.5 - 4.5 kg	5 -6 kg
	(5 - 7 lb)	(8 - 10 lb)	(11 - 13 lb)
Door Height	Force	Force	Force
254 - 305 mm	100 N	100 N	100 N
(10 - 12 in)	(22.5 lb)	(22.5 lb)	(22.5 lb)
330 - 380 mm	100 N	100 N	150 N
(13 - 15 in)	(22.5 lb)	(22.5 lb)	(33.7 lb)
406 - 457 mm	100 N	100 N	150 N
(16 - 18 in)	(22.5 lb)	(22.5 lb)	(33.7 lb)
483 - 533 mm	100 N	150 N	
(19 - 21 in)	(22.5 lb)	(33.7 lb)	
559 - 610 mm	100 N	150 N	
(22 - 24 in)	(22.5 lb)	(33.7 lb)	



OPI ECONOMY SERIES: SOFT STAYUP HINGE

PRODUCT FEATURES:

This multipurpose stay can be used on "Drop Down" and "Lift up Doors".

- This stay will open as wide as 100°, depending on the adjustment this stay "brakes" the door as it holds in intermediate positions.
- Adjustments can be made using a 4mm allen key.
- 1 piece recommended for doors under 8 lbs. and 2 pieces for doors ranging from 8 lbs. to 16 lbs.
- Non-handed.
- Chrome plated, all metal construction.

PART # SSH-2007

CHROME PLATED EURO HINGES



Can be used for either frameless or framed cabinet applications. Opening angle can be adjusted from 45°-90°

PART # DESCRIPTION

6552-ETH-10 Euro Hinge False Front Hinge

